BHARAT SANCHAR NIGAM LIMITED

(A Government of India Enterprise)

Tender document

Name of Work:- Day to Day Maintenance and ARMO to BSNL Staff Quarters, Telephone Bhawan ,CSC and inspection quarters at PURI for the Year 2018-19. (2nd Call)

NIT No. 55/2018-19/BCD/SDE-II/BBSR

Estimated Cost. Rs. 3,93,103.00

EMD.: Rs. 7,862.00

Time: 12(Twelve) Months

Certified that this tender document contains 38(Thirty Eight) pages

Executive Engineer (Civil)
BSNL Civil Division
Bhubaneswar

Name of work: Day to Day Maintenance and ARMO to BSNL Staff Quarters ,Telephone Bhawan, CSC and inspection quarters at PURI for the Year 2018-19. (2nd Call)

INDEX

| S. No. | Details | |
|-----------|---|-------|
| 1. | Cover Page | 1 |
| 2. | Index | 2 |
| 3. | Information and instructions for bidders for e-Tendering | 3-4 |
| 4. | Declaration to be given by the tenderer | 5-5 |
| 5. | Notice Inviting e- Tender (BSNL W-6) | 6-10 |
| 6. | Percentage rate tender / Item rate tender and contract for works (BSNL W-7/8) | 11-12 |
| 7. | Correction Slip No.6 | 13-13 |
| 8. | Proforma of Schedules A to F | 14-17 |
| 9. | Additional conditions and specifications | 18-22 |
| 10. | Schedule of quantities | 23-38 |

INFORMATION AND INSTRUCTIONS FOR BIDDERS FOR e-TENDERING

The Executive Engineer(Civil), BSNL Civil Division, 3rd floor, Unit-IX, Door Sanchar Bhawan, Bhubaneswar invites item rate e-tenders on behalf of BHARAT SANCHAR NIGAM LIMITED (A Government of India Enterprise) from approved and eligible contractors of BSNL (Civil Wing) and non-BSNL registered contractors of appropriate class of Public Works Organizations like CPWD, DOP, MES, Railways and State PWD (R&B) of Odisha or any other allied department or PSU of Odisha State eligible to tender in Odisha State PWD (R&B)/ DOP/ MES/ Railways for the following work:

| | Description | |
|---------------------------------------|---------------------------------|--|
| SI. | <u>Description</u> | <u>Details</u> |
| <u>No.</u> | NUT NI - | |
| i) | NIT No. | 55/2018-19/BCD/SDE-II/BBSR. |
| ii) | Name of Work: | Day to Day Maintenance and ARMO to BSNL Staff |
| | | Quarters, Telephone Bhawan, CSC and inspection |
| | | quarters at PURI for the Year 2018-19(2nd Call) |
| | | <u>-</u> |
| iii) | Estimated Cost | Rs.3,93,103.00 (Rupees Three Lakh Ninety Three |
| | | Thousand One Hundred Three) only |
| iv) | Earnest Money | Rs.7,862.00 (Rupees Seven Thousand Eight |
| | | Hundred Sixty Two) only |
| v) | Period of Completion | 12(Twelve) Months |
| vi) | Last date and time of online | |
| \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ | | 18.00 hours on 31.10.2018 |
| | submission of tender | |
| vii) | Time and date of online | 11.30 hours on 01.11.2018 |
| | opening of Documents | |
| viii) | Time and date of opening of | |
| , | Online Financial Bids | 15.30 hours on 02.11.2018 |
| iv) | | To be submitted during office hours within a week from the |
| ix) | Period during which hard | To be submitted during office hours within a week from the |
| | copies of EMD, Registration | date of opening of Financial Bid. In case the last day happens |
| | Certificates, Undertaking and | to be closed holidays, these Documents shall be submitted on |
| | other Documents to be | the next working day |
| | submitted to Division office by | |
| | only the lowest tenderer. | |

- The intending bidder must read the terms and conditions of Tender document carefully. He should submit his bid if he considers himself eligible and he is in possession of all the certificates / documents required.
- 2. Information and Instructions for bidders for e-tendering posted on website shall form part of bid document
- 3. The bid document consisting of NIT, plans, specifications, the schedule of quantities of various types of items to be executed and the set of terms and conditions of the contract to be complied with and other necessary documents can be seen and downloaded from http://www.tenderwizard.com/BSNL or www.odisha.bsnl.co.in free of cost.
- 4. For e-tendering of this tender, BSNL has engaged e-portal maintained by M/s ITI Limited, New Delhi. Intending bidders shall have to register with M/s ITI Limited, New Delhi to participate in the tendering process. For details kindly visit website http://www.tenderwizard.com/BSNL or contact Shri SANJIB MOHAPATRA (Mobile No. 9937488749 or 7377708585). If needed they can be imparted training on online bidding process as per details available on the website.
- 5. The intending bidders must have valid class-III digital signature to submit the bid.
- 6. The bid can be submitted only after depositing e-tender Processing Fee in favour of ITI Limited and uploading the mandatory scanned documents as specified within the period of bid submission. **E-tender processing fee is non-refundable.**

- 7. Copies of eligibility documents and EMD as specified in the notice inviting tender shall be scanned and uploaded on the e-tendering website within the period of tender submission. Bidders can upload documents in the form of JPG format, PDF format and any other format as permissible by the e-tendering portal.
- 8. Bidders must ensure to quote rate of each item. The column meant for quoting rate in figures appears in dark yellow colour and the moment rate is entered, it turns sky blue. In addition to this, while selecting any of the cells a warning appears that if any cell is left blank the same shall be treated as "0". Therefore, if any cell is left blank and no rate is quoted by the bidder, rate of such item shall be treated as "0" (ZERO). After submission of the bid online the contractor can re-submit revised bid any number of times but before last time and date of submission of bid as notified.
- 9. After submission of bid online, it can be revised any number of times before specified time on last date of submission of bid. While submitting the revised bid, bidder can revise the rate of one or more item(s) any number of times (he need not re-enter rate of all the items) but before last time and date of submission of bid as notified.
- 10. Financial bids shall be opened online only for bidders for whom EMD and other documents are found in order and who are found to be eligible to bid for work. On opening date, the bidder can login and see the bid opening process. After opening of bids he will receive the competitor bid sheets.
- 11. If the contractor is found ineligible after opening of bids, his bid shall become invalid.
- 12. If any discrepancy is noticed between the eligibility documents as uploaded at the time of submission of bid and hard copies as submitted physically by the bidder, the bid shall become invalid and.
- 13. The lowest bidder shall have to submit original instrument for EMD and self-certified copies of all the scanned and uploaded documents within ONE WEEK in the office of tender opening authority.

<u>List of eligibility Documents to be scanned and uploaded within the period of bid</u> submission:

- a) Certificate of registration / enlistment order;
- b) EMD in the form of Treasury Challan/ Demand Draft/ Pay order or Banker's Cheque/ Deposit at Call Receipt/ FDR of any Scheduled Bank in favour of "Account officer (Cash), O/o General Manager Telecom District BSNL, Bhubaneswar".
- c) PAN card issued by Income Tax Department:
- d) GST registration
- e) The contractor having contract for day to day maintenance work of staff quarters colony having more than 100 no. quarters or two or more contracts for day to day maintenance work of staff quarters colonies having more than 50 Nos. quarters are not eligible to apply.

Note: No. of quarters in each staff quarters colony may be verified from concerned EE(C)

- f) An undertaking that "There is no existing contract/ agreement in my name for day to day maintenance work of staff quarter colonies having more than 100 nos. quarters and no contract for two or more works for day to day maintenance work of staff quarters which having more than 50 quarters. In case I become the lowest bidder and undertaking found false, BSNL may reject the bid and also take action to withdraw my/our enlistment/debar me/us from tendering in BSNL".
- g) Copies of Form "A" and partnership deed / memorandum of articles of association and power of attorney / authorization to the person who signs the tender in case of companies etc., If the bidder is a firm in partnership/ company,
- h) An undertaking that "In case I/we become the lowest bidder, Original instrument for EMD and self certified copies of other eligibility documents shall be deposited by me/us with the Executive Engineer calling the tender within ONE WEEK of the opening of financial bid otherwise BSNL shall reject the bid and also take action to withdraw my/our enlistment/debar me/us from tendering in BSNL."

DECLARATIONS TO BE GIVEN BY THE TENDERERS

It is to certify that

a) I /We have gone through BSNL W-8 amended up to correction Slip No.6 as available on website www.tenderwizard.com/BSNL/www.odisha.bsnl.co.in or in the office of Executive Engineer (C) and I/We agree with the terms and conditions of it and understood that it will form part of the agreement.

Date: -

Signature of the Tenderer

b) In case I/we become the lowest bidder, Original instrument for EMD and self certified copies of other eligibility documents shall be deposited by me/us with the Executive Engineer calling the tender within ONE WEEK of the opening of financial bid otherwise BSNL shall reject the bid and also take action to withdraw my/our enlistment/debar me/us from tendering in BSNL.

Date: -

Signature of the Tenderer

| <i>(</i>) | Ί, | S/o | Shri | | resident | of |
|------------|-----|------------------------------|----------|---|---------------|-----|
| | | | hereby | certify that none of my relative | e(s) as defii | ned |
| sta | ge, | it is found that the informa | tion giv | d in BSNL Civil Zone, Odisha. en by me is false/incorrect, BS eemed fit without any prior intir | SNL shall h | ave |

NOTE: - (To be certified by all the partners in case of partnership firms, by all the directors in case of companies).

| 1. | Other partners | 2. Sri | Signati _S/o Sri | Signature: |
|----|--|--|---|---|
| | | 3. Sri | _S/o Sri | _ Signature: |
| | | 4. Sri | _S/o Sri | _ Signature: |
| d) | contract/ agree colonies having for day to day quarters. In cas | ment in my name for more than 100 nos. quality maintenance work of the lower the lower and also take activation. | give an undertaking to day to day maintenanguarters and no contract of staff quarters which est bidder and undert | resident of that "There is no existing nce work of staff quarter ct for two or more works the having more than 50 aking found false, BSNL renlistment/debar me/us |

Date: -

Signature of the Tenderer

BSNLW-6

BHARAT SANCHAR NIGAM LIMITED (A GOVERNMENT OF INDIA ENTERPRISE) NOTICE INVITING e-TENDER

- 1. The Executive Engineer(Civil), BSNL Civil Division, 3rd floor, Unit-IX, Door Sanchar Bhawan, Bhubaneswar invites Item rate e-tenders are invited on behalf of BHARAT SANCHAR NIGAM LIMITED (A Government of India Enterprise) from approved and eligible contractors of BSNL (Civil Wing) and Non-BSNL contractors of appropriate class registered with Public Works Organizations like CPWD, Odisha State PWD (B&R) or any other allied department or PSU of Odisha State eligible to tender in Odisha State PWD (B & R)/ DOP/ MES/ Railways for the work of "Day to Day Maintenance and ARMO to BSNL Staff Quarters, Telephone Bhawan ,CSC and inspection quarters at PURI for the Year 2018-19." (2nd Call). The enlistment of the contractors should be valid on the last date of submission of bids. In case the last date of submission of bids is extended, the enlistment of contractor should be valid on the original date of submission of bids.
- 1.1 The work is estimated to cost Rs.3,93,103.00 (Rupees Three Lakh Ninety Three Thousand One Hundred Three) only
- 1.2 Bidders will be eligible to bid for the work provided they submit proof of their valid enlistment with appropriate authority, and have valid GST registration.
- 1.2.1 Criteria of experience for submission of bid document for Non-BSNL registered contractors of Public Works Organizations like CPWD, Odisha State PWD (B&R) or any other allied department or PSU of Odisha State eligible to tender in Odisha State PWD (B & R)/ DOP/ MES/ Railways only.
- 1.2.1.1 For works up to Rs. 7 lakhs:----NIL----
- 2. Agreement shall be drawn with the successful tenderer on prescribed Form No. BSNL W-7/8 amended up to correction slip no. 6, which is available on BSNL website www.odisha.bsnl.co.in and also as a BSNL publication in the office of the Executive Engineer (Civil) BSNL Civil Division, Bhubaneswar. Tenderer shall quote his rates as per various terms and conditions of the said form which will form part of the agreement.
- 3. The time allowed for carrying out the work will be **12**(**Twelve**) **Months** and shall be reckoned from **7**th **day** after the date of issue of work order or from the **3**rd **day** of the handing over of the site whichever is later, in accordance with phasing, if any, indicated in the tender document.
- 3.1 The site for the work shall be made available in parts/ in phases and accordingly shall be handed over.
- 4. The bid document consisting of NIT, plans, specifications, the schedule of quantities of various types of items to be executed and the set of terms and conditions of the contract to be complied with and other necessary documents can be seen and downloaded from http://www.tenderwizard.com/BSNL and the NIT & General Conditions of Contract can be seen from BSNL website www.odisha.bsnl.co.in.
- For e-tendering of this tender, BSNL has engaged e-portal maintained by M/s ITI Limited, New Delhi. Intending bidders shall have to register with M/s ITI Limited, New Delhi to participate in the tendering process. For details kindly visit website http://www.tenderwizard.com/BSNL or contact Shri SANJIB MOHAPATRA (Mobile No. 9937488749 or 7377708585). If needed they can be imparted training on online bidding process as per details available on the website.
- 5.1 The intending bidders must have valid class-III digital signature to submit the bid.
- 6. **E-Tender Processing Fee (Non-refundable):** e-Tender Processing Fee amounting to Rs. 590/- is to be paid online to the account of M/s ITI Limited through their e-gateway by credit/debit card, internet banking or RGTS/EFT facility. **E-Tender processing fee cannot**

be paid in physical form i.e. through Demand draft/ Treasury Challan/ Pay Order or Banker's Cheque etc. E-Tender processing fee is non-refundable.

7. Earnest Money of Rs.7,862.00 (Rupees Seven Thousand Eight Hundred Sixty Two) only in the form of Treasury Challan/ Demand Draft/ Pay order or Banker's Cheque/ Deposit at Call Receipt/ Fixed Deposit Receipt issued in favour of 'Account officer (Cash),O/o General Manager Telecom District BSNL, Bhubaneswar payable at Bhubaneswar shall be scanned and uploaded to the e-Tendering website within the period of bid submission.

The intending bidder has to fill the details of payment instrument for EMD such as banker's name, amount, number and date etc. in the drop down menu of the e-tendering portal. The EMD has to be scanned and uploaded to the e-Tendering website by the intending bidders within the period of bid submission.

The lowest bidder shall submit the original instrument of EMD within ONE WEEK after opening of financial bid failing which the bid shall be rejected and the agency shall be debarred from tendering in BSNL and BSNL may also take action to withdraw the enlistment of such bidder.

8. The bid can be submitted only after depositing e-tender Processing Fee in favour of M/s ITI Limited and uploading the mandatory scanned documents as specified within the period of bid submission.

Following documents are required to be scanned and uploaded by the intending bidder within the period of bid submission:

- a) Certificate of registration / enlistment order;
- b) Payment instrument for Earnest Money (EMD);
- c) PAN card issued by Income Tax Department;
- d) GST registration
- e) Copies of Form "A" and partnership deed / memorandum of articles of association and power of attorney / authorization to the person who signs the tender in case of companies etc., If the bidder is a firm in partnership/ company.
- f) An undertaking that "There is no existing contract/ agreement in my name for day to day maintenance work of staff quarter colonies having more than 100 nos. quarters and no contract for two or more works for day to day maintenance work of staff quarters which having more than 50 quarters. In case I become the lowest bidder and undertaking found false, BSNL may reject the bid and also take action to withdraw my/our enlistment/debar me/us from tendering in BSNL".
- g) An undertaking that "In case I/we become the lowest bidder, the original instrument of EMD and self certified copies of other eligibility documents shall be deposited by me/us with the Executive Engineer calling the tender within ONE WEEK of the opening of financial bid otherwise BSNL shall reject the bid and also take action to withdraw my/our enlistment/debar me/us from tendering in BSNL."
- 8.1 Bidders must ensure to quote rate of each item. The column meant for quoting rate in figures appears in dark yellow colour and the moment rate is entered, it turns sky blue. In addition to this, while selecting any of the cells a warning appears that if any cell is left blank the same shall be treated as "0". Therefore, if any cell is left blank and no rate is quoted by the bidder, rate of such item shall be treated as "0" (ZERO). After submission of the bid online the contractor can re-submit revised bid any number of times but before last time and date of submission of bid as notified.

After submission of bid online, it can be revised any number of times before specified time on last date of submission of bid. While submitting the revised bid, bidder can revise the rate of one or more item(s) any number of times (he need not re-enter rate of all the items) but before last time and date of submission of bid as notified.

- 9. (i) Last date and time of online submission of bids Up to 18.00 hours on 31.10.2018
 - (ii) Time and date of online opening of documents 11.30 hours on 01.11.2018

- 9.1 Financial bids shall be opened online only for bidders for whom EMD and other documents are found in order and who are found to be eligible to bid for work.
 Financial bids of eligible bidders shall be opened at 15.30 hours on 02.11.2018
 On financial bid opening date, eligible bidders can login and see the bid opening process.
 After opening of bids they will receive the competitor bid sheets.
- 9.2 The lowest bidder shall have to submit self-certified copies of all the scanned and uploaded documents as specified in notice inviting tender along with original instrument of EMD within ONE WEEK in the office of tender opening authority.
- 9.3 The bid submitted shall become invalid if:
 - (i) The bidder is found ineligible.
 - (ii) The bidder does not upload all the documents as stipulated in the bid document including the undertaking about submission of original instrument of EMD uploaded and undertaking that "There is no existing contract/ agreement in my name for day to day maintenance work of staff quarter colonies having more than 100 nos. quarters and no contract for two or more works for day to day maintenance work of staff quarters which having more than 50 quarters. In case I become the lowest bidder and undertaking found false, BSNL may reject the bid and also take action to withdraw my/our enlistment/debar me/us from tendering in BSNL".
 - (iii) The lowest bidder does not deposit original instrument for EMD within a week of opening of bid.
 - (iv) If any discrepancy is noticed between the documents as uploaded at the time of submission of bid and self-certified copies as submitted *physically by the lowest bidder* in the office of bid opening authority.
- 9.4 In case the eligibility credentials are not found in order at any stage i.e. before award of work or during execution of the work or after completion of the work, the contractor will be liable to be debarred from tendering in BSNL for three years including any other action under the contract or existing law. This will be without prejudice to any action that may be taken against the contractor for the work awarded to him on the basis of guestioned credentials.
- 10. The description of the work is as follows: Day to Day Maintenance and ARMO to BSNL Staff Quarters, Telephone Bhawan, CSC and inspection quarters at PURI for the Year 2018-19. (2nd Call)
- 10.1 Intending Bidders are advised to inspect and examine the site and its surroundings and satisfy themselves before submitting their bids as to the nature of the ground and sub-soil (so far as is practicable), the form and nature of the site, the means of access to the site, the accommodation they may require and in general shall themselves obtain all necessary information as to risks, contingencies and other circumstances which may influence or affect their bid. A bidder shall be deemed to have full knowledge of the site whether he inspects it or not and no extra charge consequent on any misunderstanding or otherwise shall be allowed.

The bidder shall be responsible for arranging and maintaining at his own cost all materials, tools & plants, water, electricity access, facilities for workers and all other services required for executing the work unless otherwise specifically provided for in the contract documents. Submission of a bid by a bidder implies that he has read this notice and all other contract documents and has made himself aware of the scope and specifications of the work to be done and of conditions and rates at which stores, tools and plant, etc. will be issued to him by the Government and local conditions and other factors having a bearing on the execution of the work.

- 11. The competent authority on behalf of BHARAT SANCHAR NIGAM LIMITED does not bind itself to accept the lowest or any other bid and reserves to itself the authority to reject any or all the bids received without the assignment of any reason. All bids in which any of the prescribed condition is not fulfilled or any condition including that of conditional rebate is put forth by the bidders shall be summarily rejected.
- 12. Canvassing whether directly or indirectly, in connection with bidders is strictly prohibited and the bids submitted by the contractors who resort to canvassing will be liable for rejection.
- 13. The competent authority on behalf of BHARAT SANCHAR NIGAM LIMITED reserves to himself the right of accepting the whole or any part of the bid and the bidders shall be bound to perform the same at the rate quoted.

- 14. The company or firm or any other person shall not be permitted to tender for works in BSNL Civil Zone in which his near relative(s) (directly recruited or on deputation in BSNL) is/ are posted in any capacity either non-executive or executive employee. Near relative (s) for this purpose is/are defined as:
 - (i) Member of Hindu Undivided family (HUF).
 - (ii) They are Husband and Wife.
 - (iii) The one is related to other in the manner as father, mother, son(s) & Son's wife (daughter-in-law), Daughter(s), Daughter's husband (son-in-law), brother(s), brother's wife, sister(s), sister's husband (brother-in-law).

The contractor shall also intimate the names of persons who are working with him in any capacity or are subsequently employed by him and who are near relative to any executive employee/ Gazetted officer in the BSNL or Department of Telecom or in the Ministry of Communications.

All the intending tenderers will have to give a certificate that none of his/her such near relative(s) as defined above is/are working in the concerned BSNL Civil Zone where he is going to apply for tender/work. The format of the certificate is as under:

"I, ______ s/o Shri _____ Resident of_____ hereby certify that none of my relative (s) as defined above is/are employed in concerned BSNL Civil Zone. In case at any stage, it is found that the information given by me is false/incorrect, BSNL shall have the absolute right to take any action as deemed fit without any prior intimation to me".

The certificate in case of Proprietorship Firm shall be given by the proprietor; for Partnership Firm certificate shall be given by all partners and in case of Limited Company by all Directors of the company. However, Government of India/Financial Institutions nominees and independent non-official part-time Directors appointed by Govt. of India or the Governor of the State are excluded from the purview of submission of this certificate while submitting tenders by Limited Companies.

Any breach of these conditions by the Company or Firm or any other person, the tender/work will be cancelled and Earnest Money/ Security Deposit/ Performance guarantee will be forfeited at any stage, whenever it is so noticed. BSNL will not pay any damages to the company or Firm or the concerned person but damages arising on account of such cancellation to be borne by the contractor. The Company or Firm or the person will also be debarred for further participation in the tender in the concerned BSNL Civil Zone. Further, any breach of this condition by the tenderer would also render him liable to be removed from the approved list of contractors or BSNL. If however the contractor is registered in any other Department he shall also be debarred from tendering in BSNL for any breach of this condition.

- 15. No Engineer of Gazetted rank or other Gazetted Officer employed in engineering or administrative duties in an Engineering Department of the Government of India/State Government or PSU's is allowed to work as a contractor for a period of two years after his retirement from Govt. service, without previous permission of the Govt. of India or BSNL in writing. This contract is liable to be cancelled if either the contractor or any of his employees is found any time to be such a person who had not obtained the permission of the Govt. of India/State Government or PSU's as aforesaid before submission of the tender or engagement in the contractor's service.
- 16. The tender for the work shall remain open for acceptance for a period of **30(Thirty)** days from the date of opening of the tenders. If any tenderer withdraws his tender before the said period or issue of letter of acceptance/intent, whichever is earlier, or, makes any modifications in the terms and conditions of the tender which are not acceptable to the BSNL, then the BSNL shall, without prejudice to any other right or remedy, be at liberty to forfeit 50% of the said earnest money as aforesaid.
- 17. In case of works having estimated cost put to tender below Rs. 15,00,000/-, the successful tenderer shall be required to execute an agreement with the Engineer-in-charge in the Performa annexed to the tender document, within 15 days of the issue of letter of award by the BSNL. In the event of failure on the part of the successful tenderer to sign the agreement, the earnest money will be forfeited and tender cancelled.

In case of works with estimated cost put to tender Rs.15,00,000/- and above, the successful tenderer, upon issue of letter of acceptance of Tender, shall be required to furnish Performance Guarantee @ 5% of the tendered value in the form of irrevocable Bank

Guarantee of requisite amount to the Engineer-in-charge in the Performa annexed to the tender document, within 15 days of the issue of letter of acceptance of tender by BSNL. In the event of failure on the part of the successful tenderer to furnish the Bank Guarantee within 15 days, including extended period if any, the earnest money deposited by the contractor shall be forfeited automatically without any notice to the contractor, and tender will be cancelled.

- 18. This Notice Inviting Tender (BSNL W-6) shall form a part of the Contract Document. In accordance with clause 1 of the contract, the letter of acceptance shall be issued first in favour of the successful Tenderer/Contractor. After submission of the performance guarantee, the letter of award shall be issued. The contract shall be deemed to have come into effect on issue of letter of acceptance of the tender. On issue of letter of award, the successful Tenderer/Contractor shall, within 30 days from such date, formally sign the agreement consisting of:
 - a) The Notice Inviting Tender, all the documents including additional conditions, specifications and drawings, if any, forming part of the bid as uploaded at the time of invitation of bid and the rates quoted online at the time of submission of bid and acceptance thereof together with any correspondence leading thereto.
 - b) Standard BSNL W-7/8 as on BSNL website www.odisha.bsnl.co.in
 - c) Agreement signed on non-judicial stamp paper as per Performa annexed to the tender document.
- 19. Payment to the contractors shall be made through e-payment system like ECS & EFT as detailed below:
 - (a) In cities/areas where ECS/EFT facility is provided by Banks, the tenderer must have Account in such ECS/EFT facility providing Banks and that Bank A/c No shall be quoted in the tender by the tenderer
 - (b) The cost of ECS/EFT will be borne by BSNL in all cases where the payment to contractor is made in a local Branch i.e. tenderer is having bank account in the same place from where the payment is made by BSNL unit.
 - (c) In case payment is made to outside branch i.e. tenderer is having bank account not in the same place from where the payment is made by BSNL unit, the crediting cost will have to be borne by the tenderer only.
 - (d) The payments to contractors will compulsorily be made through ECS/EFT in respect of all contracts where the value of the contract is more than Rs. 10 lakhs.
- 20. First running account bill shall be paid only after
 - a) signing of the Agreement/Contract by both the parties, and
 - b) progress chart has been prepared as required under Clause 5 and approved by the competent authority.
- 21. General conditions of contract for works in BHARAT SANCHAR NIGAM LIMITED are available on BSNL website www.odisha.bsnl.co.in as well as in the Division Office.
- 22. If any terms and conditions under General Rules and Directions, (which can be seen in general conditions of contract available in BSNL website www.odisha.bsnl.co.in is in contravention to terms and conditions as above, the terms and conditions as above shall prevail.

Signature and Name of

Executive Engineer (Civil)
For & on behalf of
Bharat Sanchar Nigam Limited

BSNL W - 7/8

BHARAT SANCHAR NIGAM LIMITED (A GOVERNMENT OF INDIA ENTERPRISE)

STATE: ODISHA CIRCLE: BHUBANESWAR DIVISION: BHUBANESWAR

ZONE: ODISHA SUB-DIVISION: No. II- BBSR

Percentage Rate Tender / Item Rate Tender & Contract for Works

E-Tender for the work of "Day to Day Maintenance and ARMO to BSNL Staff Quarters, Telephone Bhawan, CSC and inspection quarters at PURI for the Year 2018-19." (2nd Call)

To be submitted online by 18.00 hours on 31.10.2018

- (i) Time and date of online opening of Documents 11.30 hours on 01.11.2018
- (ii) Time and date of opening of online Financial Bids 15.30 hours on 02.11.2018

TENDER

I/ We have read and examined notice inviting tender, schedule, A, B, C, D, E & F. specifications applicable, Drawings & Design, General Rules and Directions, Conditions of Contract, Clauses of Contract, Special conditions, Schedule of Rate & other documents forming part of the bid as uploaded at the time of invitation of bid and the rates quoted online at the time of submission of bid and Rules referred to in the Conditions of Contract and all other contents in the tender document for the work.

I/ We hereby tender for the execution of the work specified for the Bharat Sanchar Nigam Limited within the time specified in schedule 'F', viz., schedule of quantities and in accordance in all respects with the specifications, designs, drawings and instructions in writing referred to in Rule-1 of General Rules and Directions and in Clause 11 of the Conditions of the contract and with such materials as are provided for, by and in respect in accordance with, such conditions so far as applicable.

I/ We agree to keep the tender open for **30 (Thirty)** days from the due date of submission thereof and not to make any modifications in its terms and conditions. If I/we withdraw my/our tender before the said period or issue of letter of acceptance/intent, whichever is earlier, or, makes any modifications in the terms and conditions of the tender which are not acceptable to the BSNL, then the BSNL shall, without prejudice to any other right or remedy, be at liberty to forfeit 50% of the said earnest money as aforesaid.

A sum of Rs.7,862.00 (Rupees Seven Thousand Eight Hundred Sixty Two) only has been deposited in prescribed manner as earnest money. If I/We fail to commence the work specified, I/We agree that the said Bharat Sanchar Nigam Limited shall without prejudice to any other right or remedy, be at liberty to forfeit the said earnest money absolutely otherwise the said earnest money shall be retained by competent authority on behalf of the Bharat Sanchar Nigam Limited towards Security Deposit to execute all the works referred to in the tender documents upon the terms and conditions contained or referred to therein and carry out such deviations as may be ordered, upto maximum of the percentage mentioned in Schedule 'F' and those in excess of that limit at the rates to be determined in accordance with the provision contained in Clause 12.2 and 12.3 of the tender form.

I/ We hereby intimate that for receiving payments I/we have an account where the ECS/EFT facility of e-payment is available and details of same shall be intimated after issue of letter of acceptance.

I/We hereby declare that I/We shall treat the tender documents drawings and other records connected with the work as secret/confidential documents and shall not communicate information

derived there-from to any person other than a person to whom I/We am/are authorised to communicate the same or use the information in any manner prejudicial to the safety of the State.

I/We agree that should I/We fail to commence the work specified in the above memorandum, an amount equal to the amount of the earnest money mentioned in the form of invitation of tender shall be absolutely forfeited to the Bharat Sanchar Nigam Limited and the same may at the option of the competent authority on behalf of the Bharat Sanchar Nigam Limited be recovered without prejudice to any right or remedy available in law out of the deposit in so far as the same may extend in terms of the said bond and in the event of deficiency out of any other money due to me/us under this contract or otherwise.

The information in respect of works in hand is as per proforma enclosed.

| Court Jurisdiction: "I/we agree that this cont Bhubaneswar only." (Where the NIT/Tender has be | |
|--|---|
| Dated Witness: Address: Occupation: | () Signature of Contractor Postal Address: - ******* |
| ACCEPT | ANCE |
| The above tender (as modified by you (Contract hereunder) is accepted by me for and on behalf of the Rs(Rupees | |
| The letters referred to below shall form part of this (a)(b) | Contract Agreement:- |
| For & on beha | If of the Bharat Sanchar Nigam Limited. |
| | Signature |

Dated.....

Name and designation

Correction Slip no. 6 (To GCC for civil works-2006)

| No change. Engineer-in- ill as far as The amount admissible will as far as |
|--|
| ill as far as The amount admissible will as far as |
| possible be paid by 30 th working day after the day of presentation of the bill by the contractor to the Engineer in-Charge or his Asstt. Engineer together with the account of the material issued by the BSNL, or dismantled materials, if any. In the case of works outside the headquarter of the Engineer-in-Charge, the period of thirty working days will be extended to forty five working days. No change |
| a e it |

PROFORMA OF SCHEDULES

(Operative Schedules to be supplied separately to each of the intending tenderer)

SCHEDULE "A"

Schedule of Quantities - ENCLOSED

SCHEDULE "B"

Schedule of Materials to be issued to the contractor

| S. No. | Description of Item | Quantity | Rates in figures & words at which the materials will be charged from the contractor | Place of issue | |
|--------|------------------------|----------|---|----------------|--|
| 1 | 2 | 3 | 4 | 5 | |
| NIL | | | | | |

SCHEDULE "C"

Tools and Plants to be hired to the contractor

| S. No. | Description of Item | Hire charges per day | Place of issue | |
|---------|---------------------|----------------------|----------------|--|
| 1 | 2 | 3 | 4 | |
| DELETED | | | | |

SCHEDULE "D"

Additional Conditions and specifications - Enclosed

SCHEDULE "E"

Schedule of component of Materials, Labour etc. for escalation

No escalation on material and labour is payable for this work. Clause 10C for escalation of material and labour is not applicable but clause 10CA shall remain applicable.

CLAUSE 10

| as a percent of Total Value of Work | "X" | 75 % |
|---|--------------|------|
| Component of Labour expressed as percent of Total Value of Work | " Y " | 25 % |
| Component of POL expressed as percent of Total Value of Work | "Z" | 0 % |

SCHEDULE "F"

(Reference to General Conditions of Contract)

| Name of Work | Day to Day Maintenance and ARMO to BSNL Staff Quarters, Telephone Bhawan, CSC and inspection quarters at PURI for the Year 2018-19. (2nd Call) | | | | |
|---|--|--------------|-----------|------------|--------|
| Estimated cost of Work | Rs.3,93,103.00 (Rupe Thousand One Hundred | | | Ninety | Three |
| Earnest Money Rs.7,862.00 (Rupees Severally | | n Thousand | Eight Hui | ndred Sixt | y Two) |
| Security Deposit (10 % of the tendered value for works with estimated cost put to tender up to Rs. 15Lakhs) | | Rs Rupees | | only | |

GENERAL RULES AND DIRECTIONS

| | | Executi Bhuba | ive Engineer (Civil), BSNL Civil Division, neswar |
|---|---|-------------------|---|
| Maximum percentage for quantity of items of work to be executed beyond which rates are to be determined in accordance with Clause 12.2 & 12.3 | | | 50% |
| | Definitions | | See below |
| 2(v) | Engineer-in charge | Executi Bhuban | ve Engineer (Civil), BSNL Civil Division, eswar. |
| 2(viii) | Accepting Authority | Executi Bhuban | ve Engineer (Civil), BSNL Civil Division, eswar. |
| 2(x) | Percentage on cost of materials and Labour to cover all overheads and profit. | | 10 % |
| 2(xi) | Standard Schedule of Rates | 2016 fc | Public Works Department Schedule of rates - or Delhi with up to date correction slips with rates d by 110/115 |
| 9(ii) | Standard BSNL Contract Form | | W 7/8 form as modified and up to and including ion slip No.6 |
| Clause 2 | | | • |
| Authority for fixing compensation und Clause 2 | | under | Executive Engineer (Civil), BSNL Civil Division, Bhubaneswar. |
| Clause 2 | A | | |
| Whether Clause 2A shall be applicable | | licable | NO |
| Clause 3 | A | | |
| Whether Clause 3A shall be applicable | | licable | NO |
| Clause 5 | | | |
| i) Time allowed for execution of work | | | 12(Twelve) Months |
| ii) Authority to give fair and reasonable extension of time for completion of work | | | Executive Engineer (Civil), BSNL Civil Division, Bhubaneswar. |

| Clause 6 A | |
|---|---|
| Whether Clause 6A shall be applicable | NO |
| Clause 7 | |
| Gross value of work to be done together with net payment/ adjustment of advances for materials collected, if any, since the last such payment for being eligible to interim payment | 1.50 lakh |
| Clause 10 | |
| Reinforcement steel to be used in the work shall have to be procured as below | TMT bars Manufactured by any of the primary producers such as SAIL, TISCO, RINL (VIZAG) |
| Clause 10 C | Not applicable |
| Clause 10 CA | Applicable |
| Clause 11 | |
| Specification to be followed for execution of work | CPWD Specifications Volume I & II 2009 with up to date correction slips as on the date of opening of the tender |
| Clause 12 | |
| 12.2 & 12.3 Limit for value of any item of any individual trade beyond which sub clauses (i) to (v) shall not be applicable | 50%(Fifty percent) |
| Clause 16 | |
| Competent authority for deciding reduced rates | Superintending Engineer (Civil), O/o the CE(C), BSNL Civil Odisha Zone, Bhubaneswar. |

Clause 36(i)

Requirement of Technical Staff and rate of recovery in case of non-compliance shall be as per the following table:

| Value of Work | SI. No | Minimum qualification of Technical Representative | Discipline | Designation (Principal Technical/ Technical representative) | Minimum Experience in years | Number | Rate at which be made fron contractor in not fulfilling p clause 36(i) figures | the event of |
|---|-----------|--|------------|---|--|--------|---|---------------------------------------|
| For Agreement amount upto Rs 150 lakhs | 1 | Graduate Engineer OR Diploma Engineer | Civil | Principal Technical representati ve | 2 years for Graduate Engineer OR 5 years for Diploma Engineer | 1 | Rs 15,000/- | Rs Fifteen Thousand only |
| For Agreement amount between Rs | 1 | Graduate Engineer | Civil | Principal Technical representati ve | 5 years for Graduate Engineer | 1 | Rs 25,000/- | Rs Twenty Five Thousand only |
| 150 lakhs to Rs 500 lakhs | 2 | Graduate Engineer OR Diploma Engineer | Civil | Technical representati ve | 2 years for Graduate Engineer OR 5 years for Diploma Engineer | 1 | Rs 15,000/- | Rs Fifteen Thousand only |

Clause 37(i)

| Extent of GST payable by Contractor for | GST 18% applicable, Any increase/decrease |
|---|---|
| Building and Construction works/Repair & | in the rate of GST while making payment of |
| Maintenance works | bills will be adjusted accordingly. 100% of |
| | the applicable GST is payable by |
| | contractor.(Nothing is to be reimbursed to |
| | the contractor) |

Clause 42 (i)

| (i) | Schedule / statement for determining theoretical quantities of cement | On the basis of Delhi Schedule of Rates 2016 with up to date correction slips published by CPWD | | | | | |
|------|---|---|--|--|--|--|--|
| (ii) | (ii) Variation permissible on theoretical quantities | | | | | | |
| a) | Cement for works with estimated costs put | to tender | | | | | |
| | i) not more than Rs. 5 lakhs | 3 % minus | | | | | |
| | ii) more than 5 lakhs | 2 % minus | | | | | |
| b) | Steel reinforcement and structural steel see | ctions | | | | | |
| | for each diameter, section and category. | 2 % minus | | | | | |

Star prices to be considered for escalation and recoveries

| SI. | Material | Star Price |
|-----|---|---|
| No | | (Rate in Figures and Words) |
| 1 | For Cement | Rs. 6,400/- (Rupees Six thousand Four Hundred) only/M.T |
| | For Reinforcement Steel conforming to BIS 1786 - TMT bars | Rs.57, 300/-(Rupees Fifty Seven thousand three hundred) only./M.T |

The rate for recovery under clause 42 shall be same as the Star Price

SCHEDULE 'D'

ADDITIONAL CONDITIONS AND SPECIFICATIONS

- 1. The intending tenderers shall note that the work is of urgent nature and is to be positively completed within the stipulated period. Therefore, only those Contractors who are confident and capable of carrying out the work within the stipulated period should apply for the work.
- 2. The scope of work is to attend day to day complains received from occupants of Staff Quarters in charge. The contractor or his authorized representative has to attend the maintenance office daily to take the complains received from occupants and to complete the repair and maintenance work within the required time as instructed by concerned JTO(C) /SDE(C)/ Engineer-in-charge. Necessary action may be initiated by Engineer-in-charge in case of failing to attend the complains as above.
- 3 The contractor should submit a tentative programme of working within seven days of the date of commencement of work for approval to Engineer-in-Charge. The contractor will have to work as per programme approved by the department. No claim whatsoever will be entertained on this account.
- 4. The work shall be executed and measured as per metric dimensions given in the Schedule of quantities, drawings etc. (F.P.S units wherever indicated are for guidance only).
- 5. Unless otherwise provided in the Schedule of quantities, the rates tendered by the contractor shall be all inclusive and shall apply to all heights lifts and leads and depths of the building and nothing extra shall be payable to him on this account.
- 5 Whenever any reference to any Indian Standard Specification occurs in the documents relating to this contract, the same shall be inclusive of all amendments issued thereto or revisions thereof if any, up to the date of receipt of tenders.
- 6 The contractor shall give a performance test of installations as per specifications before the work is finally accepted and nothing extra whatsoever shall be payable to contractor on this account.
- 7 The work shall be carried out in a manner complying in all respects with the requirements of relevant byelaws of the Municipal Committee / Municipal Corporation / Development Authority / Improvement Trust under the jurisdiction of which the work is to be executed or as directed by the Engineer–in-charge and nothing extra shall be paid on this account.
- 8 Other agencies doing work of electrification, external services, other building work, horticulture work etc. for this project will also simultaneously execute the works and the contractor shall afford necessary facilities for the same. The contractor shall leave such necessary holes, openings etc. for laying / burying in the work pipes, cables, conduits, clamps, boxes and hooks for fan clamps etc. as may be required for the electric and sanitary works etc. and nothing extra over the agreement rates shall be paid for the same.
- 9. Unless otherwise specified in the schedule of quantities the rates for all items of the work shall be considered as inclusive of pumping out or bailing out water, if required, for which no extra payment will be made. This will include water encountered from any source, such as rains, floods, sub-soil water being high due to any other cause whatsoever.
- 10. It is likely that work is executed in restricted areas and some restrictions may be imposed by the security staff etc., on the working and / or movement of labour, materials etc., the contractor shall be bound to follow all such restrictions / instructions and nothing extra shall be payable on this account.
- 11. Wherever the work site is in non-BSNL premises, the contractor shall take extra precautions for avoiding damages to the building/ premises. The Engineer-in-charge shall be indemnified against any claims on account of damages to the building/ premises of the landlord and

- contractor shall be legally responsible for compensating the landlord as may be assessed by the Engineer-in-charge.
- 12. Any cement slurry added over base surface (or) for continuation of concreting, for better bond is added to have been in built in the item (unless otherwise / explicitly stated) and nothing extra shall be payable (or) extra cement considered with consumption on this account.
- 13. The rate for all items in which the use of cement is involved is inclusive of charges for curing.
- 14. The contractor shall give a performance test of the entire installation (s) as per standard specifications before the work is finally accepted and nothing extra whatsoever shall be payable to the contractor for the test.
- 15. Cement bags shall be stored in separate go downs to be constructed by contractor at his own cost as per sketch at page 23 of CPWD specifications 2009 Vol. II with weather proof roofs and walls.
- 16. The foundation trenches shall be kept free from water while all the works below ground level are in progress.
- 17. The contractor shall provide at his own cost suitable weighing and measuring arrangements at site for checking the weight / dimensions as may be necessary for execution of the work.
- 18. The rate for all items of work, shall, unless clearly specified otherwise include cost of all labour, material and other incidentals involved in the execution of the items.
- 19. Normally no departmental materials shall be issued to the contractor for the work. However the Engineer-in-charge may, at his discretion, issue some materials to the contractor for the work. The materials so issued shall be got insured against loss/damages etc. The contractor shall also ensure that only the required quantities of the departmental materials are used for the work. In the event of excess consumption beyond the required quantities, the Engineer-in-charge shall have the right to make recovery at market rates for which certificate of Engineer-in-charge shall be final and binding.
- 20. All materials which are to be tested for use in work shall be procured well in advance so that enough time is available for testing and approval of these materials by the Engineer-incharge.
- 21. The contractor shall also construct a sample unit complete in all respects within three months from the date of award of work and this sample unit shall be got approved by the Engineer-in-charge before mass construction is taken up. No extra claim whatsoever beyond the payments due at agreement rates will be entertained from the contractor on this account.
- 22. The contractor shall take instructions from the Engineer-in-charge regarding collection and stacking of materials in any place. No excavated earth or building material shall be stacked on areas where other buildings, roads, services or compound walls are to be constructed.
- 23. Royalty / seigniorage at the prevalent rates shall have to be paid by the contractor on the boulders, metal, shingle, sand and bajri etc. or any other material where royalty / seigniorage is payable collected by him for the execution of the work direct to the revenue / mines authority of the State Government concerned and nothing extra whatsoever shall be payable to contractor on this account.
- 24. The contractor shall make his own arrangements for obtaining electric / water connections, if required, and make necessary payments directly to the Department concerned.

- 25. The contractor shall take all precautions to avoid all accidents by exhibiting necessary day and night caution boards, speed limit board, red flag, red lights and by providing barriers. He shall be responsible for all damages and accidents caused due to negligence in this regard. No hindrance shall be caused to Traffic during the execution of work.
- 26. The contractor shall maintain in perfect condition all works executed till the completion of the entire work allotted to him. Where phased delivery is contemplated the provisions mentioned above will apply to each phase.
- 27. No compensation/payment shall be payable to the contractor for any damage caused by rains, snow fall, lightning, wind, storm, floods tornadoes, earthquakes or other natural calamities during execution of work. He will make good all such damages at his own cost and no claim on this account will be entertained.
- 28. All materials obtained by the contractor shall be got checked from Engineer-in-charge or his representative on receipt of the same at site before they are actually used.
- 29. The contractor shall clear the site thoroughly of all scaffoldings, materials and rubbish etc. left out of his work and dress the site around the building to the satisfaction of the Engineer-in-charge before the work is considered as complete.
- 30. If as per municipal rules the huts for labour are not to be erected at the site of work by the contractors, the contractors are required to provide such accommodation as is acceptable to local bodies and nothing extra shall be paid on this account.
- 31. The centering and shuttering required for RCC work will be brought to site by the contractor well in advance so that the progress of the upper floors is not hampered due to non-availability of the same. Nothing extra shall be paid for this.
- 32. The contractor must see the proposed site for the work and study specifications and conditions carefully before tendering. No claim of any sort shall be entertained on account of any site conditions or ignorance of specifications and conditions.
- 33. The tenderer should see the approaches and conditions of the site. If any approach from main road is required at the site or existing approach is to be improved and maintained for cartage and materials by the contractors, the same shall be provided, improved and maintained by the contractor at his own cost.
- 34. Cess under Building and other Construction Worker's Welfare Cess Act 1996 and other construction workers cess rules (Not withstanding anything contained in this contract) shall be recovered from the gross amount of the bill/bills at the rate stipulated under Claude 3(1) of the Building and other Construction Worker's Welfare Cess Act 1996.
- 35. The contractor shall bear all incidental charges for cartage of material required for work and construct suitable go downs, yards at the site of work for storing all the materials so as to be safe against damage by sun, rain, dampness fire, theft etc. at his own cost and also employ necessary watch and ward establishment for the purpose at his own cost.
- 36.In the item of RCC walls, railing and roofs etc., nothing extra shall be paid for making designs as per patterns given by Architects or for thickness of sections.
- 37. The rates for railing are inclusive of all the labour and the materials including execution as given in the description of the item, portion of the railings which is embedded in the masonry or RCC shall not be included for measurements.
- 38. Apart from OPC-43 grade cement as specified in General Conditions of Contract, OPC-53 grade conforming to IS: 12269 or PSC Portland Slag Cement conforming to IS: 455-1989 or PPC conforming to IS: 1489(Part-1) may also be used in the work. However, while using Portland Pozzolana cement (fly ash blended) conforming to IS: 1489(Part-1), the certificate

- from PPC manufacturer indicating the percentage of fly ash shall be submitted to the Engineer-in-charge before using the cement in the work
- In case of OPC-53 grade cement, it shall be ensured that the curing of the concrete work starts just after 4 hours of casting of concrete.
- 39. The compaction of the concrete shall be done by vibrating, table or external vibrator, as approved by Engineer-in-charge. The rate quoted for the item shall include the element of both for form work and mechanical vibration.
- 40. The water will be tested with regard to its suitability for use in RCC work and nothing extra will be paid for on this account.
- 41. The rate of item of reinforcement in RCC work includes all operations including straightening, cutting, bending, binding with annealed steel wire and placing in position at all the floors with all leads and lifts complete.
- 42. The rate of items of flooring is inclusive of providing sunk flooring in bath rooms, Kitchen etc., and nothing extra on this account is admissible.
- 43. The rate of T/ angle iron frame shall include the following:-
- 44.a) M.S. sill / tie of 16 mm dia. bar shall be welded to T-iron door frames to keep the frame vertical in correct position. The sill / tie shall be embedded in floor concrete. No tie is necessary for window frames. In the case of window frame 2 lugs 15 X 3 mm long shall be welded to each vertical member of the frame.
 - b) Each T-iron frame for doors shall have 4 nos. M.S. lugs 15 X3 mm, 10 cms long welded to each vertical member of the frame. In case of window frames, two lugs 15 X 3 mm shall be welded to each vertical member of the frame.
 - c) M.S flat 8 X 25 mm, 100 mm, long having threaded holes (No. of flats shall correspond to the No. of butt hinges to be fixed to door / window shutter) shall be welded at appropriate places at the back of the T-iron frames for fixing the required butt hinges to the frame with machine screws. M.S flats 8 X 25 mm, 50 mm long with threaded holes, shall be welded to the back of the T- sections to receive the butt hinges for the cleats.
- 45. The M.S flat clamps 15 X 6 mm thick for holding arrangements are to be provided and added as per site conditions. The rate is inclusive of the cost of such cramps.
- 46. The sill tie, lugs, curtain brackets and flats welded for fixing hinges and cleats shall not be measured for the purpose of payment.
- 47. All welding steel work shall be tested for quality of weld as laid down in IS:822 1970 before actual erection. Wherever welding appears it shall mean continuous fillet welding.
- 48. Sanitary fittings, paints, and other materials shall be obtained from one of the firms on the list of approved manufacturers of C.P.W.D. and shall bear I.S.I mark. The materials shall be tested as per provision in relevant I.S codes. The contractor's rates for items involving the use of the above materials shall be deemed to cover the cost of samples.
- 49. The contractor shall be responsible for the protection of the sanitary and water supply fittings and other fittings and fixtures against pilferage and breakage during the period of installation and thereafter until the building is handed over.
- 50. Water tanks, taps, pipes, fittings and accessories should conform to the CPWD specifications 2009 Vol. I to Vol. II with up to date correction slips, byelaws and specifications of the Municipal bodies Corporations etc. The contractor should engage licensed plumbers for the work and get the material (fixtures fittings) tested by the municipal bodies / corporation authorities wherever required, at his own cost. The work shall be carried out according to the municipal byelaws.

- 51. The work of water supply, internal sanitary installations and drainage work etc., shall be carried out as per local Municipal Corporation or such local body byelaws and the contractor shall produce necessary completion certificate from such authorities after completion of the work.
- 52. The contractor shall comply with proper and legal orders and directions of the local or public authority or municipality and abide by their rules and regulations and pay all fees and charges which he may be liable.
- 53. The sanitary water supply and drainage pipes and fittings and other materials shall be of approved quality shall conform to the relevant C.P.W.D. specifications 2009 Vol. I to Vol. II with up to date correction slips and shall be I.S.I marked. The work shall be carried out without infringing on any of local Municipal byelaws.
- 54. The contractor shall procure steel reinforcement bars confirming to relevant BIS codes from main producers as approved by the Ministry of Steel.

CONTRACTOR

EXECUTIVE ENGINEER(C)

CONDITIONS FOR OTHER TAXES AND ROYALTIES

- 1. The rates offered should be inclusive of GST liable to be paid by contractors(either directly payable by them or through BSNL .GST rate is mentioned under clause 37(i) in the schedule F. Any increase in the rate of GST while making payment of bills will be compensated to the contractor. Any decrease in the rate of GST while making payment of bills will be recovered from the bills of contractor .Contribution towards EPF, ESIC and all other taxes as applicable. Insurance, loading, unloading, transportation etc should be included on the quoted rates. The rate shall be firm & final.
- 2. **Income Tax and surcharges** over Income Tax etc. at the rates fixed by the Ministry of Finance. Government of India shall be deducted from all the running and final bills of the contractor. Should there be any increase in rate of Income Tax and surcharge during execution of the contract, the same shall be payable by the contractor
- 3. Cost for the welfare of construction workers shall also be deducted from the bills of the contractors.
- 4. **Royalty** shall have to be paid by the contractor on all materials such as stone, bricks, boulders, metal, shingle, bajri, stone aggregate, coarse sand and fine sand etc. or any other materials used for the execution of the work direct to the Revenue Authority of the District/ State Govt. concerned.

SCHEDULE OF QUANTITIES

Name of the work: Day to Day Maintenance and ARMO to BSNL Staff Quarters, Telephone Bhawan, CSC and inspection quarters at PURI for the Year 2018-19.

| SI. No. | Description of Item | Quantity | Unit | Rate (Rs) | Amount(Rs) |
|------------|--|----------|------------------------|-----------|------------|
| | Sub-Head : Earth Work | | | | |
| 1 | Earth work in surface excavation not exceeding 30 cm in depth but exceeding 1.5 m in width as well as 10 sqm on plan including getting out and disposal of excavated earth upto 50 m and lift up to 1.5 m, as directed by Engineer-in-Charge: | | | | |
| a) | All kinds of soil | 60.00 | One Square Metre | | |
| 2 | Clearing jungle including uprooting of rank vegetation, grass, brush wood, trees and saplings of girth up to 30 cm measured at a height of 1 m above ground level and removal of rubbish up to a distance of 50m outside the periphery of the area cleared. Sub-Head: Concrete Work | 700.00 | One Square Metre | | |
| 3 | Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work | | | | |
| a) | up to plinth level: 1:2:4 (1 cement : 2 coarse sand(zone-III) : 4 | 0.30 | One Cubic | | |
| u, | graded stone aggregate 20 mm nominal size) | 0.50 | Metre | | |
| b) | 1:5:10 (1 cement : 5 coarse sand(zone-III) : 10 graded stone aggregate 40 mm nominal size) | 0.50 | One Cubic Metre | | |
| 4 | Extra for providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. | 5.00 | per 50 kg cement | | |
| | Sub-Head : Reinforced Cement Concrete | | | | |
| 5 | Reinforced cement concrete work in beams, suspended floors, roofs having slope up to 15° landings, balconies, shelves, chajjas, lintels, bands, plain window sills, staircases and spiral stair cases above plinth level up to floor five level, excluding the cost of centering, shuttering, finishing and reinforcement, with 1:1.5:3 (1 cement: 1.5 coarse sand (zone-III): 3 graded stone aggregate 20 mm nominal size). | 0.15 | One Cubic Metre | | |
| 6 | Centering and shuttering including strutting, propping etc. and removal of form for all heights: | | | | |

| a) | Suspended floors, roofs, landings, balconies and access platform. | 2.00 | One Square Metre | |
|-----|--|-------|------------------------|--|
| 7 | Providing, hoisting and fixing above plinth level up to floor five level precast reinforced cement concrete work in string courses, bands, copings, bed plates, anchor blocks, plain window sills and the like, including the cost of required centering, shuttering but, excluding cost of reinforcement, with 1:1.5:3 (1 cement: 1.5 coarse sand (zone-III): 3 graded stone aggregate 20mmnominal size). | 0.10 | One Cubic Metre | |
| 8 | Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete up to plinth level. | | | |
| a) | Thermo-Mechanically Treated bars of grade Fe-500 D or more. | 30.00 | One Kilogram | |
| 9 | Smooth finishing of the exposed surface of R.C.C. work with 6 mm thick cement mortar 1:3 (1 Cement : 3 fine sand) | 5.00 | One Square Metre | |
| | Sub-Head : Brick Work | | | |
| 10 | Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in foundation and plinth in: | | | |
| a) | Cement mortar 1:4 (1 cement : 4 coarse sand) | 0.40 | One Cubic Metre | |
| | Sub-Head: Wood and P.V.C. Work | | | |
| 11 | Providing wood work in frames of doors, windows, clerestory windows and other frames, wrought framed and fixed in position with hold fast lugs or with dash fasteners of required dia. & length (hold fast lugs or dash fastener shall be paid for separately). | | | |
| a) | Sal wood | 0.15 | One Cubic Metre | |
| 12 | Providing and fixing panelled or panelled and glazed shutters for doors, windows and clerestory windows, including ISI marked M.S. pressed butt hinges bright finished of required size with necessary screws, excluding panelling which will be paid for separately, all complete as per direction of Engineer-in-charge. | | | |
| a) | Kiln seasoned and chemically treated hollock wood. | | | |
| (i) | 30 mm thick shutters | 3.00 | One Square Metre | |

| 13 | Providing and fixing panelling or panelling | | | |
|----------|---|------|------------|---|
| | and glazing in panelled or panelled and | | | |
| | glazed shutters for doors, windows and | | | |
| | clerestory windows (Area of opening for | | | |
| | panel inserts excluding portion inside | | | |
| | grooves or rebates to be measured). | | | |
| | Panelling for panelled or panelled and | | | |
| | glazed shutters 25 mm to 40 mm thick: | | | |
| a) | Kiln seasoned and chemically treated | 2.00 | One Square | |
| | hollock wood. | | Metre | |
| 14 | Providing and fixing ISI marked flush door | | | |
| | shutters conforming to IS: 2202 (Part I) non- | | | |
| | decorative type, core of block board | | | |
| | construction with frame of 1st class hard | | | |
| | wood and well matched commercial 3 ply | | | |
| | veneering with vertical grains or cross bands | | | |
| | and face veneers on both faces of shutters : | | | |
| a) | 30 mm thick including ISI marked Stainless | 4.00 | One Square | |
| ", | Steel butt hinges with necessary screws. | 7.00 | Metre | |
| 15 | Providing and fixing 50 mm bright finished | 4.00 | Each | |
| 13 | brass cup board or wardrobe knob of | 4.00 | Lacii | |
| | approved quality with necessary screws | | | |
| | | | | |
| 16 | Providing and fixing aluminium extruded | 5.00 | Each | |
| | section body tubular type universal | | | |
| | hydraulic door closer (having brand logo | | | |
| | with IS: 3564, embossed on the body, door | | | |
| | weight upto 36 kg to 80 kg and door width | | | |
| | from 701 mm to 1000 mm) with double | | | |
| | speed adjustment with necessary | | | |
| | accessories and screws etc. complete. | | | |
| 17 | Providing and fixing chromium plated brass | 1.00 | Each | |
| | 100 mm mortice latch and lock with 6 levers | | | |
| | and a pair of lever handles of approved | | | |
| | quality with necessary screws etc. complete. | | | |
| 18 | Providing and fixing aluminium sliding door | | | |
| | bolts ISI marked anodised (anodic coating | | | |
| | not less than grade AC 10 as per IS: 1868) | | | |
| | transparent or dyed to required colour or | | | |
| | shade with nuts and screws etc. complete: | | | |
| 2) | 250x16 mm | 6.00 | Each | - |
| a) | | 6.00 | Each | |
| 19 | Providing and fixing aluminium tower bolts | | | |
| | ISI marked anodised (anodic coating not less | | | |
| | than grade AC 10 as per IS : 1868) | | | |
| | transparent or dyed to required colour or | | | |
| | shade with necessary screws etc. complete: | | | |
| a) | 200x10 mm | 8.00 | Each | |
| b) | 150x10 mm | 5.00 | Each | |
| <u> </u> | | | I | 1 |

| | T | | | 1 |
|----|---|-------|--------|------|
| 20 | Providing and fixing aluminium handles ISI | | | |
| | marked anodised (anodic coating not less | | | |
| | than grade AC 10 as per IS : 1868) | | | |
| | transparent or dyed to required colour or | | | |
| | shade with necessary screws etc. complete: | | | |
| a) | 100 mm | 8.00 | Each | |
| 21 | Providing and fixing aluminium hanging | | | |
| | floor door stopper ISI marked anodised | | | |
| | (anodic coating not less than grade AC 10 as | | | |
| | per IS: 1868)transparent or dyed to | | | |
| | required colour and shade with necessary | | | |
| | screws etc. complete. | | | |
| a) | Twin rubber stopper | 5.00 | Each | |
| 22 | Providing and fixing bright finished 100 mm | 1.00 | Each | |
| | mortice lock with 6 levers without pair of | | | |
| | handles of approved quality for aluminium | | | |
| | door, with necessary screws etc complete as | | | |
| | per direction of Engineer-in-charge. | | | |
| 23 | Providing and fixing Fiber Glass Reinforced | 10.00 | One | |
| | plastic (FRP) Door Frames of cross-section | | Metre | |
| | 90 mm x 45 mm having single rebate of 32 | | | |
| | mm x 15 mm to receive shutter of 30 mm | | | |
| | thickness. The laminate shall be moulded | | | |
| | with fire resistant grade unsaturated | | | |
| | polyester resin and chopped mat. Door | | | |
| | frame laminate shall be 2 mm thick and | | | |
| | shall be filled with suitable wooden block in | | | |
| | all the three legs. The frame shall be | | | |
| | covered with fiber glass from all sides. M.S. | | | |
| | stay shall be provided at the bottom to | | | |
| | steady] the frame. | | | |
| 24 | Providing and fixing to existing door frames. | | | |
| a) | 30 mm thick Glass Fibre Reinforced Plastic | 5.00 | One | |
| | (FRP) panelled door shutter of required | | Square | |
| | colour and approved brand and | | Metre | |
| | manufacture, made with fire - retardant | | | |
| | grade unsaturated polyester resin, moulded | | | |
| | to 3 mm thick FRP laminate for forming | | | |
| | hollow rails and styles, with wooden frame | | | |
| | and suitable blocks of seasoned wood inside | | | |
| | at required places for fixing of fittings, cast | | | |
| | monolithically with 5 mm thick FRP laminate | | | |
| | for panels conforming to IS: 14856, | | | |
| | including fixing to frames. | | | |
| | | | | |

| | | | T | T | , |
|----------|---|-------|----------|---|---|
| 25 | Providing and fixing factory made uPVC | | | | |
| | white colour sliding glazed window upto | | | | |
| | 1.50m in height dimension comprising of | | | | |
| | uPVC multi-chambered frame with in built | | | | |
| | roller track and sash extruded profiles duly | | | | |
| | reinforced with 1.60 ± 0.2 mm thick | | | | |
| | galvanized mild steel section made from roll | | | | |
| | forming process of required length (shape & | | | | |
| | size according to uPVC profile), appropriate | | | | |
| | dimension of uPVC extruded glazing beads | | | | |
| | and uPVC extruded interlocks, EPDM gasket, | | | | |
| | wool pile, zinc alloy (white powder coated) | | | | |
| | touch locks with hook , zinc alloy body with | | | | |
| | single nylon rollers(weight bearing capacity | | | | |
| | to be 40 kg), G.I fasteners 100 x 8 mm size | | | | |
| | for fixing frame to finished wall and | | | | |
| | necessary stainless steel screws etc. | | | | |
| | Profile of frame & sash shall be mitred cut | | | | |
| | and fusion welded at all corners including | | | | |
| | drilling of holes for fixing hardware's and | | | | |
| | drainage of water etc. After fixing frame the | | | | |
| | gap between frame and adjacent finished | | | | |
| | wall shall be filled with weather proof | | | | |
| | silicon sealant over backer rod of required | | | | |
| | size and of approved quality, all complete as | | | | |
| | per approved drawing & direction of | | | | |
| | 1 1 | | | | |
| | Engineer-in-Charge. (Single / double glass | | | | |
| | panes, wire mesh and silicon sealant shall | | | | |
| | be paid separately) | | | | |
| | Note: For uPVC frame, and sash extruded | | | | |
| | profiles minus 5% tolerance in dimension | | | | |
| | i.e. in depth & width of profile shall be | | | | |
| <u> </u> | acceptable. | | | | |
| a) | Two track two panels sliding window made | 6.00 | One | | |
| | of (small series) frame 52 x 44 mm & sash | | Square | | |
| | 32 x 60 mm both having wall thickness of | | Metre | | |
| | 1.9 ± 0.2 mm and single glazing bead of | | | | |
| | appropriate dimension. (Area of window | | | | |
| | upto 1.75 sqm) | | | | |
| | Sub-Head : Steel Work | | | | |
| 26 | Steel work welded in built up sections/ | | | | |
| | framed work including cutting, hoisting, | | | | |
| | fixing in position and applying a priming | | | | |
| | coat of approved steel primer using | | | | |
| | structural steel etc. as required. | | | | |
| a) | In gratings, frames, guard bar, ladder, | 20.00 | One | | |
| | railings, brackets, gates and similar works. | | Kilogram | | |
| | • | | | • | |

| | | | 1 | |
|----|--|-------|------------|--|
| 27 | Providing and fixing carbon steel galvanised (minimum coating 5 micron) dash fastener of 10 mm dia double threaded 6.8 grade | | | |
| | (yield strength 480 N/mm ²), counter sunk | | | |
| | head, comprising of 10 m dia polyamide PA | | | |
| | 6 grade sleeve, including drilling of hole in | | | |
| | frame, concrete/ masonry, etc. as per | | | |
| | direction of Engineer-in-charge. | | | |
| a) | 10 x140 mm | 10.00 | Each | |
| 28 | Providing & fixing glass panes with putty | | | |
| | and glazing clips in steel doors, windows, | | | |
| | clerestory windows all complete with: | | | |
| a) | 4.0 mm thick glass panes. | 2.00 | One Square | |
| | Sub-Head : Flooring | | Metre | |
| 29 | Cement concrete flooring 1:2:4 (1 cement : | | | |
| 23 | 2 coarse sand : 4 graded stone aggregate) | | | |
| | finished with a floating coat of neat cement, | | | |
| | including cement slurry, but excluding the | | | |
| | cost of nosing of steps etc. complete. | | | |
| a) | 40 mm thick with 20 mm nominal size stone | 5.00 | One Square | |
| | aggregate | | Metre | |
| 30 | Providing and fixing 1st quality ceramic glazed | 3.00 | One | |
| | wall tiles conforming to IS: 15622 (thickness to | | Square | |
| | be specified by the manufacturer), of | | Metre | |
| | approved make, in all colours, shades except | | | |
| | burgundy, bottle green, black of any size as | | | |
| | approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick | | | |
| | bed of cement mortar 1:3 (1 cement : 3coarse | | | |
| | sand) and jointing with grey cement slurry @ | | | |
| | 3.3kg per sqm, including pointing in white | | | |
| | cement mixed with pigment of matching | | | |
| | shade complete | | | |
| 31 | Providing and laying rectified Glazed Ceramic | 6.00 | One | |
| | floor tiles of size 300x300mm or more | | Square | |
| | (thickness to be specified by the | | Metre | |
| | manufacturer), of 1stquality conforming to IS: 15622, of approved make, in colours White, | | | |
| | Ivory, Grey, Fume Red Brown, laid on 20 mm | | | |
| | thick cement mortar 1:4(1 Cement: 4 Coarse | | | |
| | sand), jointing with grey cement slurry @ | | | |
| | 3.3kg/sqm including grouting the joints with | | | |
| | white cement and matching pigments etc., | | | |
| | complete. | | | |
| | Sub-Head : Roofing | | | |
| 32 | Providing gola 75x75mm in cement | | | |
| | concrete 1:2:4 (1 cement :2 coarse sand : 4 | | | |
| | stone aggregate 10 mm and down gauge) | | | |
| | including finishing with cement mortar 1:3(1 | | | |
| | cement : 3 fine sand) as per standard design | | | |

| a) | In 75x75mm deep chase | 12.00 | One Running | |
|----------|--|--------|----------------------|--|
| 33 a) | Providing and fixing on wall face unplasticised Rigid PVC rain water pipes conforming to IS: 13592 Type A, including jointing with seal ring conforming to IS: 5382, leaving 10 mm gap for thermal expansion, (i)Single socketed pipes. 75 mm diameter | 10.00 | Metre One Running | |
| b) | 110 mm diameter | 8.00 | Metre One Running | |
| 34 | Providing and fixing on wall face unplasticised - PVC moulded fittings/accessories for unplasticised Rigid PVC rain water pipes conforming to IS: 13592 Type A including jointing with seal ring conforming to IS:5382 leaving 10 mm gap for thermal expansion. | | Metre | |
| a) | Bend 87.5° | | | |
| (i) | 75 mm bend | 4.00 | Each | |
| (ii) | 110 mm bend | 2.00 | Each | |
| 35 | Providing and fixing unplasticised -PVC pipe clips of approved design to unplasticised - PVC rain water pipes by means of 50x50x50mm hardwood plugs, screwed with M.S. screws of required length including cutting brick work and fixing in cement mortar 1:4 (1 cement : 4 coarse sand) and making good the wall etc. complete. | | | |
| a) | 75 mm | 6.00 | Each | |
| b) | 110 mm | 8.00 | Each | |
| | Sub-Head : Finishing | 0.00 | Lacii | |
| 36 | 12 mm cement plaster of mix : | | | |
| a) | 1:4 (1 cement: 4 coarse sand) | 15.00 | One Square Metre | |
| 37 | Neat cement punning | 15.00 | One Square Metre | |
| 38 | Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: | | | |
| a) | Two or more coats on new work. | 40.00 | One Square Metre | |
| 39 | Distempering with 1st quality acrylic distemper, having VOC (Volatile Organic Compound) content less than 50 grams/litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour. | | | |
| a) | One coat. | 350.00 | One Square Metre | |
| b) | Two coats. | 40.00 | One Square Metre | |

| | Sub-Head : Repairs to Buildings | | | |
|-----|--|--------|---------------------|--|
| 40 | Repairs to plaster of thickness 12 mm to 20 | | | |
| | mm in patches of area 2.5 sq. meters and | | | |
| | under, including cutting the patch in proper | | | |
| | shape, raking out joints and preparing and | | | |
| | plastering the surface of the walls complete, | | | |
| | including disposal of rubbish to the dumping | | | |
| | ground within 50 metres lead : | | | |
| a) | With cement mortar 1:4 (1 cement : 4 fine sand). | 15.00 | One Square Metre | |
| 41 | Renewing glass panes, with wooden fillets wherever necessary: | | | |
| a) | Float glass panes of thickness 4 mm . | 2.00 | One Square Metre | |
| 42 | White washing with lime to give an even shade: | | | |
| a) | Old work (one or more coats) . | 200.00 | One Square Metre | |
| 43 | Painting with synthetic enamel paint of | | | |
| | approved brand and manufacture of | | | |
| | required colour to give an even shade: | | | |
| a) | One or more coats on old work. | 120.00 | One Square Metre | |
| 44 | Finishing walls with Acrylic Smooth exterior | | | |
| | paint of required shade : | | | |
| a) | Old work (One or more coat applied @ 0.90 ltr/10 sqm). | 50.00 | One Square Metre | |
| 45 | Disconnecting damaged overhead/terrace | 1.00 | Each | |
| | PVC water storage tank of any size from | | | |
| | water supply line and removing from the | | | |
| | terrace including shifting at ground level as | | | |
| 1.0 | per direction of Engineer-in- charge. | 2.00 | Each | |
| 46 | Dismantling W.C. Pan of all sizes including disposal of dismantled materials i/c malba | 3.00 | EdCII | |
| | all complete as per directions of Engineer- | | | |
| | in- Charge. | | | |
| | Sub-Head : Dismantling and Demolishing | | | |
| 47 | Demolishing cement concrete manually/ by | | | |
| | mechanical means including disposal of | | | |
| | material within 50 metres lead as per | | | |
| | direction of Engineer - in - charge. | | | |
| a) | Nominal concrete 1:3:6 or richer mix (i/c | 0.20 | One Cubic | |
| | equivalent design mix) | | Metre | |
| b) | Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix) | 1.00 | One Cubic Metre | |
| 48 | Dismantling doors, windows and clerestory | | | |
| | windows (steel or wood) shutter including | | | |
| | chowkhats, architrave, holdfasts etc. complete | | | |
| | and stacking within 50 metres lead : | | | |
| a) | Of area 3 sq. metres and below | 8.00 | Each | |

| 49 Taking out doors, windows and clerestory window shutters (steel or wood) including stacking within 50 metres lead: a) Of area 3 sq. metres and below 50 Dismantling of flushing cistern of all types (CLI/PVC/Vitreous China) including stacking of useful materials near the site and disposal of unserviceable materials within 50 metres lead. 51 Dismantling aluminium/ Gypsum partitions, doors, windows, fixed glazing and false ceiling including disposal of unserviceable material with in 50 meters lead as directed by Engineer-in-charge. 52 Disposal of building rubbish / malba / similar unserviceables, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved. 53 Disposal of fixing white vitreous china water closet squatting pan (Indian type): a) Orissa pattern W.C. pan of size 580x440 mm 54 Providing and fixing white vitreous china pedestal type (European type/ wash down type) water closet squatting pan (Indian type): a) Orissa pattern W.C. pan of size 580x440 mm 55 Providing and fixing white vitreous china gedestal type (European type/ wash down type) water closet squatting pan (Indian type): a) Orissa pattern W.C. pan of size 580x440 mm 56 Providing and fixing P.V.C. low level flushing cistern with manually controlled device (handle lever) conforming to 15 : 7231, with all fittings and fixtures complete: a) White solid plastic seat with lid 57 Providing and fixing shile vitreous china hack or wall corner type lipped front urinal back or wall corner type lipped front urinal | | <u></u> | | | ı | |
|--|----------------------|--|-------|--------------|---|--|
| Dismantling of flushing cistern of all types (C.I./PVC/Vitreous China) including stacking of useful materials near the site and disposal of unserviceable materials within 50 metres lead. | 49 | | | | | |
| Dismantling of flushing cistern of all types (C.I./PVC/Vitreous China) including stacking of useful materials near the site and disposal of unserviceable materials within 50 metres lead. | a) | Of area 3 sq. metres and below | 3.00 | Each | | |
| doors, windows, fixed glazing and false ceiling including disposal of unserviceable surplus material and stacking of serviceable material with in 50 meters lead as directed by Engineer-in-charge. 52 Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved. 53 Providing and fixing white vitreous china water closet squatting pan (Indian type): a) Orissa pattern W.C. pan of size 580x440 mm 54 Providing and fixing white vitreous china pedestal type (European type/ wash down type) water closet pan. 55 Providing and fixing P.V.C. low level flushing cistern with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixing solid plastic seat with lid for pedestal type W.C. pan complete: a) 10 litre capacity - White 56 Providing and fixing solid plastic seat with lid for pedestal type W.C. pan complete: a) White solid plastic seat with lid 57 Providing and fixing white vitreous china flat back or wall corner type lipped front urinal basin of 430x260x350 mm or 340x410x265 mm sizes respectively. 58 Providing and fixing white vitreous china wash basin including making all connections but excluding the cost of fittings: | | Dismantling of flushing cistern of all types (C.I./PVC/Vitreous China) including stacking of useful materials near the site and disposal of unserviceable materials within | 4.00 | Each | | |
| similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved. Sub-Head: Sanitary Installations Providing and fixing white vitreous china water closet squatting pan (Indian type): a) Orissa pattern W.C. pan of size 580x440 mm Providing and fixing white vitreous china pedestal type (European type/ wash down type) water closet pan. 55 Providing and fixing P.V.C. low level flushing cistern with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures complete. a) 10 litre capacity - White 56 Providing and fixing solid plastic seat with lid for pedestal type W.C. pan complete: a) White solid plastic seat with lid 57 Providing and fixing white vitreous china flat back or wall corner type lipped front urinal basin of 430x260x350 mm or 340x410x265 mm sizes respectively. 58 Providing and fixing white vitreous china wash basin including making all connections but excluding the cost of fittings: | 51 | doors, windows, fixed glazing and false ceiling including disposal of unserviceable surplus material and stacking of serviceable material with in 50 meters lead as directed | 25.00 | Square | | |
| Providing and fixing white vitreous china water closet squatting pan (Indian type): a) Orissa pattern W.C. pan of size 580x440 mm 3.00 Each Providing and fixing white vitreous china pedestal type (European type/ wash down type) water closet pan. 55 Providing and fixing P.V.C. low level flushing cistern with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures complete. a) 10 litre capacity - White 3.00 Each 56 Providing and fixing solid plastic seat with lid for pedestal type W.C. pan complete: a) White solid plastic seat with lid 3.00 Each 57 Providing and fixing white vitreous china back or wall corner type lipped front urinal basin of 430x260x350 mm or 340x410x265 mm sizes respectively. 58 Providing and fixing white vitreous china wash basin including making all connections but excluding the cost of fittings: | 52 | similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts | 20.00 | Cubic | | |
| Providing and fixing white vitreous china water closet squatting pan (Indian type): a) Orissa pattern W.C. pan of size 580x440 mm 3.00 Each Providing and fixing white vitreous china pedestal type (European type/ wash down type) water closet pan. 55 Providing and fixing P.V.C. low level flushing cistern with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures complete. a) 10 litre capacity - White 3.00 Each 56 Providing and fixing solid plastic seat with lid for pedestal type W.C. pan complete: a) White solid plastic seat with lid 3.00 Each 57 Providing and fixing white vitreous china back or wall corner type lipped front urinal basin of 430x260x350 mm or 340x410x265 mm sizes respectively. 58 Providing and fixing white vitreous china wash basin including making all connections but excluding the cost of fittings: | | Sub-Head : Sanitary Installations | | | | |
| Providing and fixing white vitreous china pedestal type (European type/ wash down type) water closet pan. Providing and fixing P.V.C. low level flushing cistern with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures complete. a) 10 litre capacity - White Providing and fixing solid plastic seat with lid for pedestal type W.C. pan complete: a) White solid plastic seat with lid Providing and fixing white vitreous china flat back or wall corner type lipped front urinal basin of 430x260x350 mm or 340x410x265 mm sizes respectively. Providing and fixing white vitreous china wash basin including making all connections but excluding the cost of fittings: | 53 | Providing and fixing white vitreous china | | | | |
| pedestal type (European type/ wash down type) water closet pan. 55 Providing and fixing P.V.C. low level flushing cistern with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures complete. a) 10 litre capacity - White 3.00 Each 56 Providing and fixing solid plastic seat with lid for pedestal type W.C. pan complete: a) White solid plastic seat with lid 3.00 Each 57 Providing and fixing white vitreous china flat back or wall corner type lipped front urinal basin of 430x260x350 mm or 340x410x265 mm sizes respectively. 58 Providing and fixing white vitreous china wash basin including making all connections but excluding the cost of fittings: | a) | Orissa pattern W.C. pan of size 580x440 mm | 3.00 | Each | | |
| cistern with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures complete. a) 10 litre capacity - White 56 Providing and fixing solid plastic seat with lid for pedestal type W.C. pan complete: a) White solid plastic seat with lid 57 Providing and fixing white vitreous china flat back or wall corner type lipped front urinal basin of 430x260x350 mm or 340x410x265 mm sizes respectively. 58 Providing and fixing white vitreous china wash basin including making all connections but excluding the cost of fittings: | | | | | | |
| Providing and fixing solid plastic seat with lid for pedestal type W.C. pan complete: a) White solid plastic seat with lid 57 Providing and fixing white vitreous china flat back or wall corner type lipped front urinal basin of 430x260x350 mm or 340x410x265 mm sizes respectively. 58 Providing and fixing white vitreous china wash basin including making all connections but excluding the cost of fittings: | 54 | pedestal type (European type/ wash down | 1.00 | Each | | |
| lid for pedestal type W.C. pan complete: a) White solid plastic seat with lid 57 Providing and fixing white vitreous china flat back or wall corner type lipped front urinal basin of 430x260x350 mm or 340x410x265 mm sizes respectively. 58 Providing and fixing white vitreous china wash basin including making all connections but excluding the cost of fittings: | | pedestal type (European type/ wash down type) water closet pan. Providing and fixing P.V.C. low level flushing cistern with manually controlled device (handle lever) conforming to IS: 7231, with | 1.00 | Each | | |
| 57 Providing and fixing white vitreous china flat back or wall corner type lipped front urinal basin of 430x260x350 mm or 340x410x265 mm sizes respectively. 58 Providing and fixing white vitreous china wash basin including making all connections but excluding the cost of fittings: | 55 | pedestal type (European type/ wash down type) water closet pan. Providing and fixing P.V.C. low level flushing cistern with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures complete. | | | | |
| back or wall corner type lipped front urinal basin of 430x260x350 mm or 340x410x265 mm sizes respectively. 58 Providing and fixing white vitreous china wash basin including making all connections but excluding the cost of fittings: | 55 a) | pedestal type (European type/ wash down type) water closet pan. Providing and fixing P.V.C. low level flushing cistern with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures complete. 10 litre capacity - White Providing and fixing solid plastic seat with | | | | |
| wash basin including making all connections but excluding the cost of fittings : | 3) 56 | pedestal type (European type/ wash down type) water closet pan. Providing and fixing P.V.C. low level flushing cistern with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures complete. 10 litre capacity - White Providing and fixing solid plastic seat with lid for pedestal type W.C. pan complete: | 3.00 | Each | | |
| | 55 a) 56 a) | pedestal type (European type/ wash down type) water closet pan. Providing and fixing P.V.C. low level flushing cistern with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures complete. 10 litre capacity - White Providing and fixing solid plastic seat with lid for pedestal type W.C. pan complete: White solid plastic seat with lid Providing and fixing white vitreous china flat back or wall corner type lipped front urinal basin of 430x260x350 mm or 340x410x265 | 3.00 | Each Each | | |
| | 55 a) 56 a) | pedestal type (European type/ wash down type) water closet pan. Providing and fixing P.V.C. low level flushing cistern with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures complete. 10 litre capacity - White Providing and fixing solid plastic seat with lid for pedestal type W.C. pan complete: White solid plastic seat with lid Providing and fixing white vitreous china flat back or wall corner type lipped front urinal basin of 430x260x350 mm or 340x410x265 mm sizes respectively. Providing and fixing white vitreous china wash basin including making all connections | 3.00 | Each Each | | |

| 59 | Providing and fixing P.V.C. waste pipe for sink or wash basin including P.V.C. waste fittings complete. | | | |
|------|--|------|----------------------|--|
| a) | Flexible pipe | | | |
| (i) | 32 mm dia | 3.00 | Each | |
| (ii) | 40 mm dia | 3.00 | Each | |
| 60 | Providing and fixing 600x450 mm beveled edge mirror of superior glass (of approved quality) complete with 6 mm thick hard board ground fixed to wooden cleats with C.P. brass screws and washers complete. | 5.00 | Each | |
| 61 | Providing and fixing mirror of superior glass (of approved quality) and of required shape and size with plastic moulded frame of approved make and shade with 6 mm thick hard board backing: | | | |
| a) | Rectangular shape 1500x450 mm | 1.00 | Each | |
| 62 | Providing and fixing soil, waste and vent pipes: | | | |
| a) | 100 mm dia. | | | |
| (i) | Sand cast iron S&S pipe as per IS: 1729. | 6.00 | One Running Metre | |
| 63 | Providing and fixing plain bend of required degree. | | | |
| a) | 100 mm dia | | | |
| (i) | Sand cast iron S&S as per IS - 1729 | 1.00 | Each | |
| 64 | Providing and fixing single equal plain junction of required degree with access door, insertion rubber washer 3 mm thick, bolts and nuts complete. | | | |
| a) | 100x100x100 mm | | | |
| (i) | Sand cast iron S&S as per IS - 1729 | 1.00 | Each | |
| 65 | Providing and fixing terminal guard: | | | |
| a) | 100 mm | | | |
| (i) | Sand cast iron S&S as per IS - 1729 | 1.00 | Each | |
| | Sub-Head : Water Supply | | | |
| 66 | Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge. : Internal work - Exposed on wall | | | |

| a) 20 mm nominal outer dia. Pipes. b) 25 mm nominal outer dia. Pipes. c) 32 mm nominal outer dia. Pipes. d) 40 mm nominal outer dia. Pipes. d) 40 mm nominal outer dia. Pipes. d) 40 mm nominal outer dia. Pipes. e) 50 mm nominal outer dia. Pipes. f) Froviding and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end): a) 25 mm nominal bore d) 40 mm nominal bore d) 65 mm nominal bore d) 68 Providing and placing on terrace (at all floor levels) polyethylene water storage tank ISI: 12701 marked, with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank. d) Circular tank f) Circular tank f) Circular tank f) Providing and fixing C.P. brass bib cock of approved quality conforming to IS:8931: a) 15 mm nominal bore d) Providing and fixing C.P. brass stop cock (concealed) of standard design and of approved make conforming to IS:8931. a) 15 mm nominal bore. d) Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 a) 15 mm nominal bore. d) Providing and fixing PTMT bib cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long, Weighing not less than 88 gms. 73 Providing and fixing PTMT stop cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long, Weighing not less than 88 gms. 74 Providing and fixing PTMT pillar cock of approved quality and colour. a) 15 mm nominal bore, 70 mm long, Weighing not less than 88 gms. 74 Providing and fixing PTMT pillar cock of approved quality and colour. a) 15 mm nominal bore, 107 mm long, Weighing not less than 10 gms. | | | | | |
|---|----|--|---------|-----------|--|
| c) 32 mm nominal outer dia. Pipes. d) 40 mm nominal outer dia. Pipes. e) 50 mm nominal outer dia. Pipes. 15.00 One funning Metre With C.I. wheel of approved quality (screwed end): a) 25 mm nominal bore b) 40 mm nominal bore c) 50 mm nominal bore c) 50 mm nominal bore d) 65 mm nominal bore d) 68 Providing and placing on terrace (at all floor levels) polyethylene water storage tank ISI 12701 marked, with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank. a) Circular tank for Providing and fixing C.P. brass bib cock of approved quality conforming to IS:8931: a) 15 mm nominal bore 4.00 Each 70 Providing and fixing C.P. brass stop cock (concealed) of standard design and of approved make conforming to IS:8931. a) 15 mm nominal bore. 71 Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 a) 15 mm nominal bore a) 15 mm nominal bore 71 Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 a) 15 mm nominal bore a) 15 mm nominal bore 72 Providing and fixing PTMT bib cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. Weighing not less than 88 gms. 73 Providing and fixing PTMT stop cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. Providing and fixing PTMT pillar cock of approved quality and colour. b) 15 mm nominal bore, 86 mm long. Providing and fixing PTMT pillar cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. Providing and fixing PTMT pillar cock of approved quality and colour. b) 15 mm nominal bore, 107 mm long. 10.00 Each | a) | 20 mm nominal outer dia. Pipes. | 10.00 | _ | |
| d) 40 mm nominal outer dia. Pipes. e) 50 mm nominal outer dia. Pipes. 70 Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end): a) 25 mm nominal bore b) 40 mm nominal bore c) 50 mm nominal bore d) 65 mm nominal bore d) 65 mm nominal bore 1.00 Each d) 65 mm nominal bore levels) polyethylene water storage tank ISI: 12701 marked, with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank. a) Circular tank Providing and fixing C.P. brass bib cock of approved quality conforming to IS:8931: a) 15 mm nominal bore. 4.00 Each 70 Providing and fixing C.P. brass stop cock (concealed) of standard design and of approved make conforming to IS:8931. a) 15 mm nominal bore. 71 Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 a) 15 mm nominal bore. a) 15 mm nominal bore. 2.00 Each 71 Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 a) 15 mm nominal bore a) 15 mm nominal bore a) 15 mm nominal bore, 86 mm long. Weighing not less than 88 gms. 72 Providing and fixing PTMT stop cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. Weighing not less than 88 gms. 74 Providing and fixing PTMT pillar cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. Weighing not less than 88 gms. | b) | 25 mm nominal outer dia .Pipes. | 20.00 | _ | |
| e) 50 mm nominal outer dia. Pipes. 67 Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end): a) 25 mm nominal bore 2.00 Each b) 40 mm nominal bore 3.00 Each c) 50 mm nominal bore 3.00 Each d) 65 mm nominal bore 1.00 Each for ilet, outer and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank. a) Circular tank 1000.00 One Litre Providing and fixing C.P. brass bib cock of approved quality conforming to IS:8931: a) 15 mm nominal bore. 4.00 Each 70 Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931. a) 15 mm nominal bore. 2.00 Each 71 Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 a) 15 mm nominal bore a) 15mm nominal bore 2.00 Each 72 Providing and fixing PTMT bib cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. Weighing not less than 88 gms. 73 Providing and fixing PTMT stop cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. Weighing not less than 88 gms. 74 Providing and fixing PTMT pillar cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. Weighing not less than 88 gms. 74 Providing and fixing PTMT pillar cock of approved quality and colour. a) 15 mm nominal bore, 107 mm long. 10.00 Each | c) | 32 mm nominal outer dia. Pipes. | 10.00 | _ | |
| 67 Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end): a) 25 mm nominal bore | d) | 40 mm nominal outer dia. Pipes. | 40.00 | _ | |
| with C.I. wheel of approved quality (screwed end): a) 25 mm nominal bore | e) | 50 mm nominal outer dia. Pipes. | 15.00 | _ | |
| b) 40 mm nominal bore 3.00 Each c) 50 mm nominal bore 3.00 Each d) 65 mm nominal bore 1.00 Each 68 Providing and placing on terrace (at all floor levels) polyethylene water storage tank ISI: 12701 marked, with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank. a) Circular tank 1000.00 One Litre Froviding and fixing C.P. brass bib cock of approved quality conforming to IS:8931: a) 15 mm nominal bore. 4.00 Each 70 Providing and fixing C.P. brass stop cock (concealed) of standard design and of approved make conforming to IS:8931. a) 15 mm nominal bore. 4.00 Each 71 Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 a) 15 mm nominal bore a) 15mm nominal bore 2.00 Each 72 Providing and fixing PTMT bib cock of approved quality and colour. a) 15mm nominal bore, 86 mm long. Weighing 12.00 Each not less than 88 gms. 73 Providing and fixing PTMT stop cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. 10.00 Each 74 Providing and fixing PTMT pillar cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. 10.00 Each | 67 | with C.I. wheel of approved quality (screwed | | | |
| c) 50 mm nominal bore 3.00 Each d) 65 mm nominal bore 1.00 Each Froviding and placing on terrace (at all floor levels) polyethylene water storage tank ISI: 12701 marked, with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank. a) Circular tank 1000.00 One Litre 69 Providing and fixing C.P. brass bib cock of approved quality conforming to IS:8931: a) 15 mm nominal bore. 4.00 Each 70 Providing and fixing C.P. brass stop cock (concealed) of standard design and of approved make conforming to IS:8931. a) 15 mm nominal bore. 4.00 Each 71 Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 a) 15 mm nominal bore a) 15mm nominal bore 72 Providing and fixing PTMT bib cock of approved quality and colour. a) 15mm nominal bore, 86 mm long. Weighing not less than 88 gms. 73 Providing and fixing PTMT stop cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. 10.00 Each 74 Providing and fixing PTMT pillar cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. 10.00 Each 75 Providing and fixing PTMT pillar cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. 10.00 Each | a) | 25 mm nominal bore | 2.00 | Each | |
| d) 65 mm nominal bore 1.00 Each Providing and placing on terrace (at all floor levels) polyethylene water storage tank ISI: 12701 marked, with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank. a) Circular tank 1000.00 One Litre 69 Providing and fixing C.P. brass bib cock of approved quality conforming to IS:8931: a) 15 mm nominal bore. 4.00 Each 70 Providing and fixing C.P. brass stop cock (concealed) of standard design and of approved make conforming to IS:8931. a) 15 mm nominal bore. 4.00 Each 71 Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 a) 15 mm nominal bore 72 Providing and fixing PTMT bib cock of approved quality and colour. a) 15mm nominal bore, 86 mm long. Weighing not less than 88 gms. 73 Providing and fixing PTMT stop cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. 10.00 Each 74 Providing and fixing PTMT pillar cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. 10.00 Each 75 Providing and fixing PTMT pillar cock of approved quality and colour. | b) | 40 mm nominal bore | 3.00 | Each | |
| Providing and placing on terrace (at all floor levels) polyethylene water storage tank ISI: 12701 marked, with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank. a) Circular tank | c) | 50 mm nominal bore | 3.00 | Each | |
| levels) polyethylene water storage tank ISI: 12701 marked, with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank. a) Circular tank | d) | 65 mm nominal bore | 1.00 | Each | |
| 69 Providing and fixing C.P. brass bib cock of approved quality conforming to IS:8931: a) 15 mm nominal bore. 4.00 Each 70 Providing and fixing C.P. brass stop cock (concealed) of standard design and of approved make conforming to IS:8931. a) 15 mm nominal bore. 4.00 Each 71 Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 a) 15 mm nominal bore a) 15mm nominal bore 2.00 Each 72 Providing and fixing PTMT bib cock of approved quality and colour. a) 15mm nominal bore, 86 mm long. Weighing not less than 88 gms. 73 Providing and fixing PTMT stop cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. Weighing not less than 88 gms. 74 Providing and fixing PTMT pillar cock of approved quality and colour. a) 15 mm nominal bore, 107 mm long. 10.00 Each | 68 | levels) polyethylene water storage tank ISI: 12701 marked, with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without | | | |
| approved quality conforming to IS:8931: a) 15 mm nominal bore. 4.00 Each 70 Providing and fixing C.P. brass stop cock (concealed) of standard design and of approved make conforming to IS:8931. a) 15 mm nominal bore. 4.00 Each 71 Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 a) 15 mm nominal bore a) 15 mm nominal bore 2.00 Each 72 Providing and fixing PTMT bib cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. Weighing not less than 88 gms. 73 Providing and fixing PTMT stop cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. Weighing not less than 88 gms. 74 Providing and fixing PTMT pillar cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. Weighing not less than 88 gms. 74 Providing and fixing PTMT pillar cock of approved quality and colour. a) 15 mm nominal bore, 107 mm long. 10.00 Each | a) | Circular tank | 1000.00 | One Litre | |
| 70 Providing and fixing C.P. brass stop cock (concealed) of standard design and of approved make conforming to IS:8931. a) 15 mm nominal bore. 71 Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 a) 15 mm nominal bore a) 15mm nominal bore 72 Providing and fixing PTMT bib cock of approved quality and colour. a) 15mm nominal bore, 86 mm long. Weighing not less than 88 gms. 73 Providing and fixing PTMT stop cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. 10.00 Each Weighing not less than 88 gms. 74 Providing and fixing PTMT pillar cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. 10.00 Each Weighing and fixing PTMT pillar cock of approved quality and colour. a) 15 mm nominal bore, 107 mm long. 10.00 Each | 69 | | | | |
| (concealed) of standard design and of approved make conforming to IS:8931. a) 15 mm nominal bore. 71 Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 a) 15 mm nominal bore a) 15mm nominal bore 72 Providing and fixing PTMT bib cock of approved quality and colour. a) 15mm nominal bore, 86 mm long. Weighing not less than 88 gms. 73 Providing and fixing PTMT stop cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. Weighing not less than 88 gms. 74 Providing and fixing PTMT pillar cock of approved quality and colour. a) 15 mm nominal bore, 107 mm long. 10.00 Each | a) | 15 mm nominal bore. | 4.00 | Each | |
| 71 Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 a) 15 mm nominal bore a) 15mm nominal bore 2.00 Each 72 Providing and fixing PTMT bib cock of approved quality and colour. a) 15mm nominal bore, 86 mm long. Weighing not less than 88 gms. 73 Providing and fixing PTMT stop cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. Weighing not less than 88 gms. 74 Providing and fixing PTMT pillar cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. 10.00 Each 75 Providing and fixing PTMT pillar cock of approved quality and colour. a) 15 mm nominal bore, 107 mm long. 10.00 Each | 70 | (concealed) of standard design and of | | | |
| for basin mixer and geyser points of approved quality conforming to IS:8931 a) 15 mm nominal bore a) 15mm nominal bore 2.00 Each 72 Providing and fixing PTMT bib cock of approved quality and colour. a) 15mm nominal bore, 86 mm long. Weighing not less than 88 gms. 73 Providing and fixing PTMT stop cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. Weighing not less than 88 gms. 74 Providing and fixing PTMT pillar cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. 10.00 Each 74 Providing and fixing PTMT pillar cock of approved quality and colour. a) 15 mm nominal bore, 107 mm long. 10.00 Each | a) | 15 mm nominal bore. | 4.00 | Each | |
| 72 Providing and fixing PTMT bib cock of approved quality and colour. a) 15mm nominal bore, 86 mm long. Weighing not less than 88 gms. 73 Providing and fixing PTMT stop cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. Weighing not less than 88 gms. 74 Providing and fixing PTMT pillar cock of approved quality and colour . a) 15mm nominal bore, 107 mm long. 10.00 Each | | for basin mixer and geyser points of approved quality conforming to IS:8931 a) | | | |
| approved quality and colour. a) 15mm nominal bore, 86 mm long. Weighing not less than 88 gms. 73 Providing and fixing PTMT stop cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. Weighing not less than 88 gms. 74 Providing and fixing PTMT pillar cock of approved quality and colour . a) 15mm nominal bore, 107 mm long. 10.00 Each | a) | 15mm nominal bore | 2.00 | Each | |
| not less than 88 gms. 73 Providing and fixing PTMT stop cock of approved quality and colour. a) 15 mm nominal bore, 86 mm long. Weighing not less than 88 gms. 74 Providing and fixing PTMT pillar cock of approved quality and colour. a) 15mm nominal bore, 107 mm long. 10.00 Each | 72 | _ | | | |
| approved quality and colour. a) 15 mm nominal bore, 86 mm long. Weighing not less than 88 gms. 74 Providing and fixing PTMT pillar cock of approved quality and colour . a) 15mm nominal bore, 107 mm long. 10.00 Each | a) | | 12.00 | Each | |
| Weighing not less than 88 gms. 74 Providing and fixing PTMT pillar cock of approved quality and colour . a) 15mm nominal bore, 107 mm long. 10.00 Each | 73 | | | | |
| approved quality and colour . a) 15mm nominal bore, 107 mm long. 10.00 Each | a) | | 10.00 | Each | |
| | 74 | | | | |
| | a) | _ | 10.00 | Each | |

| Providing and fixing PTMT swivelling shower, 15mm nominal bore. Weighing not less than 40 gms. Providing and fixing unplasticised P.V.C. connection pipe with PTMT Nuts, collar and bush of approved quality and colour. a) 15 mm nominal bore with 30 cm length. Cutting holes up to 30x30 cm in walls including making good the same: a) With common burnt clay F.P.S. (non modular) bricks. Cutting holes up to 15x15 cm in R.C.C. floors and roofs for passing drain pipe etc. and repairing the hole after insertion of drain pipe etc. with cement concrete 1:2x4 (1 cement :2 coarse sand :4 graded stone aggregate 20 mm nominal size), including finishing complete so as to make it leak proof. Making chases up to 7.5x7.5 cm in walls including making good and finishing with matching surface after housing G.I. pipe etc. Sub-Head: Drainage Making soak pit 2.5 m diameter 3.0 metre deep with 45 x 45 cm dry brick honey comb shaft with bricks and S.W. drain pipe 100 mm diameter, 1.8 m long complete as per standard design. With common burnt clay F.P.S. (non modular) bricks of class designation 7.5 Sub-Head: Aluminium Work Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / panelling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, panelling and dash fasteners to be paid for separately): a) For fixed portion | | | | | |
|--|----|--|------|-------|--|
| connection pipe with PTMT Nuts, collar and bush of approved quality and colour. a) 15 mm nominal bore with 30 cm length. 77 Cutting holes up to 30x30 cm in walls including making good the same: a) With common burnt clay F.P.S. (non modular) bricks. 78 Cutting holes up to 15x15 cm in R.C.C. floors and roofs for passing drain pipe etc. and repairing the hole after insertion of drain pipe etc. with cement concrete 1:2:4 (1 cement :2 coarse sand : 4 graded stone aggregate 20 mm nominal size), including finishing complete so as to make it leak proof. 79 Making chases up to 7.5x7.5 cm in walls including making good and finishing with matching surface after housing G.I. pipe etc. 80 Making soak pit 2.5 m diameter 3.0 metre deep with 45 x 45 cm dry brick honey comb shaft with bricks and S.W. drain pipe 100 mm diameter, 1.8 m long complete as per standard design. a) With common burnt clay F.P.S. (non modular) bricks of class designation 7.5 80 Sub-Head : Aluminium Work 81 Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to 15: 733 and 15: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium sape beading for glazing / panelling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, panelling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, panelling, and dash fasteners to be paid for separately): | 75 | shower, 15mm nominal bore. Weighing not | 5.00 | Each | |
| 77 Cutting holes up to 30x30 cm in walls including making good the same: a) With common burnt clay F.P.S. (non modular) bricks. 78 Cutting holes up to 15x15 cm in R.C.C. floors and roofs for passing drain pipe etc. and repairing the hole after insertion of drain pipe etc. with cement concrete 1:2:4 (1 cement :2 coarse sand :4 graded stone aggregate 20 mm nominal size), including finishing complete so as to make it leak proof. 79 Making chases up to 7.5x7.5 cm in walls including making good and finishing with matching surface after housing G.I. pipe etc. 80 Making soak pit 2.5 m diameter 3.0 metre deep with 45 x 45 cm dry brick honey comb shaft with bricks and S.W. drain pipe 100 mm diameter, 1.8 m long complete as per standard design. a) With common burnt clay F.P.S. (non modular) bricks of class designation 7.5 81 Sub-Head: Aluminium Work 81 Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / panelling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, panelling and dash fasteners to be paid for separately): | 76 | connection pipe with PTMT Nuts, collar and | | | |
| including making good the same: a) With common burnt clay F.P.S. (non modular) bricks. 78 Cutting holes up to 15x15 cm in R.C.C. floors and roofs for passing drain pipe etc. and repairing the hole after insertion of drain pipe etc. with cement concrete 1:2:4 (1 cement :2 coarse sand : 4 graded stone aggregate 20 mm nominal size), including finishing complete so as to make it leak proof. 79 Making chases up to 7.5x7.5 cm in walls including making good and finishing with matching surface after housing G.I. pipe etc. 80 Making soak pit 2.5 m diameter 3.0 metre deep with 45 x 45 cm dry brick honey comb shaft with bricks and S.W. drain pipe 100 mm diameter, 1.8 m long complete as per standard design. a) With common burnt clay F.P.S. (non modular) bricks of class designation 7.5 Sub-Head: Aluminium Work 81 Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / panelling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, panelling and dash fasteners to be paid for separately): | a) | 15 mm nominal bore with 30 cm length. | 5.00 | Each | |
| modular) bricks. 78 Cutting holes up to 15x15 cm in R.C.C. floors and roofs for passing drain pipe etc. and repairing the hole after insertion of drain pipe etc. with cement concrete 1:2:4 (1 cement :2 coarse sand :4 graded stone aggregate 20 mm nominal size), including firishing complete so as to make it leak proof. 79 Making chases up to 7.5x7.5 cm in walls including making good and finishing with matching surface after housing G.I. pipe etc. 79 Sub-Head: Drainage 80 Making soak pit 2.5 m diameter 3.0 metre deep with 45 x 45 cm dry brick honey comb shaft with bricks and S.W. drain pipe 100 mm diameter, 1.8 m long complete as per standard design. a) With common burnt clay F.P.S. (non modular) bricks of class designation 7.5 70 Sub-Head: Aluminium Work 81 Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required FPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / panelling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, panelling and dash fasteners to be paid for separately): | 77 | | | | |
| and roofs for passing drain pipe etc. and repairing the hole after insertion of drain pipe etc. with cement concrete 1:2:4 (1 cement :2 coarse sand : 4 graded stone aggregate 20 mm nominal size), including finishing complete so as to make it leak proof. 79 Making chases up to 7.5x7.5 cm in walls including making good and finishing with matching surface after housing G.I. pipe etc. 80 Making soak pit 2.5 m diameter 3.0 metre deep with 45 x 45 cm dry brick honey comb shaft with bricks and S.W. drain pipe 100 mm diameter, 1.8 m long complete as per standard design. a) With common burnt clay F.P.S. (non modular) bricks of class designation 7.5 Sub-Head : Aluminium Work 81 Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to 15: 733 and 15: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / panelling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, panelling and dash fasteners to be paid for separately): | a) | • | 2.00 | Each | |
| including making good and finishing with matching surface after housing G.I. pipe etc. Sub-Head: Drainage 80 Making soak pit 2.5 m diameter 3.0 metre deep with 45 x 45 cm dry brick honey comb shaft with bricks and S.W. drain pipe 100 mm diameter, 1.8 m long complete as per standard design. a) With common burnt clay F.P.S. (non modular) bricks of class designation 7.5 Sub-Head: Aluminium Work 81 Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / panelling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, panelling and dash fasteners to be paid for separately): | 78 | and roofs for passing drain pipe etc. and repairing the hole after insertion of drain pipe etc. with cement concrete 1:2:4 (1 cement :2 coarse sand : 4 graded stone aggregate 20 mm nominal size), including finishing complete so | 1.00 | Each | |
| matching surface after housing G.I. pipe etc. Sub-Head: Drainage 80 Making soak pit 2.5 m diameter 3.0 metre deep with 45 x 45 cm dry brick honey comb shaft with bricks and S.W. drain pipe 100 mm diameter, 1.8 m long complete as per standard design. a) With common burnt clay F.P.S. (non modular) bricks of class designation 7.5 Sub-Head: Aluminium Work 81 Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / panelling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, panelling and dash fasteners to be paid for separately): | 79 | Making chases up to 7.5x7.5 cm in walls | 3.00 | One | |
| Sub-Head: Drainage 80 Making soak pit 2.5 m diameter 3.0 metre deep with 45 x 45 cm dry brick honey comb shaft with bricks and S.W. drain pipe 100 mm diameter, 1.8 m long complete as per standard design. a) With common burnt clay F.P.S. (non modular) bricks of class designation 7.5 Sub-Head: Aluminium Work 81 Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / panelling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, panelling and dash fasteners to be paid for separately): | | | | _ | |
| Making soak pit 2.5 m diameter 3.0 metre deep with 45 x 45 cm dry brick honey comb shaft with bricks and S.W. drain pipe 100 mm diameter, 1.8 m long complete as per standard design. a) With common burnt clay F.P.S. (non modular) bricks of class designation 7.5 Sub-Head : Aluminium Work 81 Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / panelling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, panelling and dash fasteners to be paid for separately): | | matching surface after housing G.I. pipe etc. | | Metre | |
| deep with 45 x 45 cm dry brick honey comb shaft with bricks and S.W. drain pipe 100 mm diameter, 1.8 m long complete as per standard design. a) With common burnt clay F.P.S. (non modular) bricks of class designation 7.5 Sub-Head : Aluminium Work 81 Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / panelling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, panelling and dash fasteners to be paid for separately): | | Sub-Head : Drainage | | | |
| Sub-Head: Aluminium Work 81 Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / panelling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, panelling and dash fasteners to be paid for separately): | | deep with 45 x 45 cm dry brick honey comb shaft with bricks and S.W. drain pipe 100 mm diameter, 1.8 m long complete as per standard design. | | | |
| Sub-Head: Aluminium Work Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / panelling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, panelling and dash fasteners to be paid for separately): | a) | , | 1.00 | Each | |
| Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / panelling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, panelling and dash fasteners to be paid for separately): | | | | | |
| a) Tot fixed portion | | Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / panelling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, panelling and dash fasteners to be paid for separately): | | | |
| | a) | For fixed portion | | | |

| (1) | | | | - |
|----------|--|-------|---------------------|---|
| (i) | Anodised aluminium (anodised transparent or | 10.00 | One | |
| | dyed to required shade according to IS: 1868, | | Kilogram | |
| | Minimum anodic coating of grade AC 15) | | | |
| b) | For shutters of doors, windows & ventilators | | | |
| | including providing and fixing hinges/ pivots | | | |
| | and making provision for fixing of fittings | | | |
| | wherever required including the cost of EPDM | | | |
| | rubber / neoprene gasket required (Fittings | | | |
| | shall be paid for separately). | | _ | |
| (i) | Anodised aluminium (anodised transparent or | 7.00 | One | |
| | dyed to required shade according to IS: 1868, | | Kilogram | |
| | Minimum anodic coating of grade AC 15) | | | |
| 82 | Providing and fixing 12mm thick pre- | | | |
| | laminated particle board flat pressed three | | | |
| | layer or graded wood particle board | | | |
| | conforming to IS:12823 Grade I Type II, in | | | |
| | panelling fixed in aluminum doors, windows | | | |
| | shutters and partition frames with C.P. brass / | | | |
| | stainless steel screws etc. complete as per | | | |
| | architectural drawings and directions of | | | |
| | engineer-in-charge. | | | |
| a) | Pre-laminated particle board with decorative | 2.00 | One Square | |
| | lamination on both sides. | | Metre | |
| 83 | Providing and fixing glazing in aluminium | | | |
| | door, window, ventilator shutters and | | | |
| | partitions etc. with EPDM rubber / neoprene | | | |
| | gasket etc. complete as per the architectural | | | |
| | drawings and the directions of engineer-in- | | | |
| | charge . (Cost of aluminium snap beading shall | | | |
| | be paid in basic item): | | | |
| a) | With float glass panes of 4.0 mm thickness | 2.00 | One Square Metre | |
| 84 | Providing and fixing aluminium round shape | | | |
| | handle of outer dia 100mm with SS screws etc. | | | |
| | complete as per direction of Engineer-in-charge | | | |
| a) | Anodized (AC 15) aluminium | 2.00 | Each | |
| | Sub-Head : Water Proofing | | | |
| 85 | Grading roof for water proofing treatment | | | |
| | with | | | |
| a) | Cement mortar 1:3 (1 cement : 3 coarse sand) | 0.50 | One Cubic | |
| <u> </u> | | | Metre | |
| | Sub-Head : LMR Items | | | |
| 86 | Repairing to aluminium door/window shutter by | 2.00 | Each | |
| | opening all joints, frames if required and cutting | | | |
| | the members to required length, providing and | | | |
| | fixing aluminium angle cleats, hinges & dash | | | |
| | fastener, if required and rearranging the pivots | | | |
| | etc. for smooth operation of the Aluminium | | | |
| | doors as per direction of the Engineer-in-charge. | | | |
| 87 | Easing and adjusting of doors, windows, | 20.00 | Each | |
| | clerestory window shutters by sawing and | | | |
| | tightening of screws in hinges etc. complete as | | | |
| | per direction of Engineer-in-charge. | | | |

| 88 | Repairing wooden shutters of doors, windows, clerestory windows & cupboards of any size at all floor levels after taking out the same & replacing damaged members such as styles and rails with new Piasal or equivalent local hard wood members and refixing the same after making the shutter good and operational along with renewing hinges wherever required etc complete as per direction of Engineer-in-charge. | | | |
|----|--|-------|------------------------|--|
| a) | With well seasoned piasal or equivalent local hard wood | 5.00 | Each | |
| 89 | Repositioning/ shifting of partitions by dismantling the extruded aluminium tubular sections and other sections of doors, windows including fixing in place with dash fasteners of required dia and size and necessary filling up the gaps at junctions, i.e. at top, bottom & sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be cleaned, straightened, mitred and jointed wherever required including cleat angle, Aluminium snap beading for glazing / panelling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (new aluminium members/glazing/panelling and dash fasteners to be paid for separately) | 25.00 | One Square Metre | |
| 90 | Checking and making good all leakages by applying solvent cement or m-seal / cement mortar etc. in G.I/ PVC/SCI/CI pipes etc. complete as per direction of Engineer-incharge (New fittings to be paid for separately). The rate shall be inclusive of material costs, labour charges, tools and plants, equipments and incidentals all complete. | 10.00 | per job | |
| 91 | Repairing of flushing cistern by replacing damaged parts such as float/ siphon etc. with new parts as per requirement all complete as per direction of Engineer-in-charge. | 8.00 | Each | |
| 92 | Providing and fixing premium quality CP brass pillar cock with aerator like Jaguar (CQT23011) or equivalent make as per direction of Engineer in charge. | | | |
| a) | 15 mm nominal size | 5.00 | Each | |
| 93 | Providing and fixing hand shower (health faucet ALD-CHR 565) of Jaquar or equivalent with 8 mm diameter, 1.00 metre long easy flex tube in chrome finish and wall hook with necessary SS / CP brass screws complete as per direction of Engineer-in-charge. | 2.00 | Each | |

| | | Т | | 1 |
|-----|--|--------|--------------------|---|
| 94 | Cleaning and disinfecting overhead water tanks/ underground sump by bailing / pumping out dirty water, brushing the inside surface for removing mush, algae etc effectively with the help of bleaching powder, washing and flushing the inside with sufficient water including disposal of waste with in a lead of 50 metre all complete as per direction of Engineer-in-charge. | 40.00 | One Cubic Metre | |
| 95 | Providing and fixing C.P.brass wall mixer of Jaquar (product code: CON-267KN) or equivalent make with hand shower arrangement with connecting legs, wall flanges and wall bracket for hand shower including dismantling the existing defective wall mixer and refixing the serviceable hand shower etc complete as per direction of Engineer-in-charge. | 1.00 | Each | |
| 96 | Providing and fixing C.P.brass central hole basin mixer without popup waste system with 450 mm long braided hoses of Jaquar (product code: CON-167KNB) or equivalent make including dismantling the existing defective basin mixer etc complete as per direction of Engineer-in-charge. | 1.00 | Each | |
| 97 | Repairing C.P.brass / brass bib cock / stop cock / pillar cock by replacing defective spindle with washer etc complete as per direction of Engineer-in-charge. | 20.00 | Each | |
| 98 | Cleaning of open surface drains of any size including removal of debrishes, sullage and disposal within a lead of 50 metre all complete as per direction of Engineer-incharge. | 300.00 | One Metre | |
| 99 | Cleaning of manholes along with sewer line including removing the waste, sludge deposits along with flushing with sufficient water all complete as per direction of Engineer-in-charge. | 35.00 | Each | |
| 100 | Uprooting trees and plants from roof and walls or other building parts including applying acid and making good the damages with cement concrete or mortar so as to match with the surrounding surface. The rate includes all materials, labour, T&P, scaffolding and disposal of debrishes in the municipal dumping ground. | 50.00 | Each | |
| 101 | Providing and fixing polyethylene cover with suitable locking arrangement of Sintex or equivalent make on existing polyethylene water storage tank on terrace (at all floor levels) including supplying required screws or nuts and bolts etc complete as per direction of Engineer-in-charge. | 2.00 | Each | |

| 102 | Trimming of trunks and branches of trees to required shape taking all precautionary measures & disposal of rubbish at specified locations all complete as per the direction of the engineer in charge. Cleaning of septic tank by cesspool tanker by sucking all liquid & sludge and disposal of | 10.00 | Each | |
|-----|---|-------|------------------------|--|
| | same beyond the municipal area including all labour, tools, and plants etc. complete as per direction of Engineer-in-charge. | | | |
| a) | Per trip of cesspool tanker including required sewermen to agitate the sludge with the liquid for easy suction. | 8.00 | Each | |
| 104 | Cleaning/ dechocking of soak pit by cesspool tanker by sucking all liquid & sludge and disposal of same beyond the municipal area. This include all labour, tools, and plants etc. towards removing the soak pit cover and minor rectifications to the pit if required and placing the cover it its position all complete as per direction of Engineer-in-charge. | 1.00 | Each | |
| 105 | Deduct for taking into possession the unserviceable dismantled materials: | | | |
| a) | Brass/GM Full way valve | 9.00 | Each | |
| b) | CP brass pillar tap | 5.00 | Each | |
| c) | Brass/ CP brass bib cock/ stop cock | 10.00 | Each | |
| d) | GI Pipes of any dia | 10.00 | Each | |
| e) | Old unserviceable wooden member pieces | 20.00 | One Kilogram | |
| f) | Old unserviceable wooden/ panelled (ply/wood)/ flush door/window/ cupboard shutters etc of any thickness. | 5.00 | One Square Metre | |
| g) | Old unserviceable health faucet | 2.00 | Each | |

For & on behalf of the Bharat Sanchar Nigam Limited

CONTRACTOR

Executive Engineer(C)
BSNL Civil Division
Bhubaneswar